

County Surveyor's Record, Douglas County, Oregon

18700

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS																	
26.20	Spur, slopes S. 60° E.; continue to ascend over S. slope.																
33.80	Dirt road, 25 lks. wide, bears N. 35° E. and S. 35° W.																
39.950	<p>The cor. of secs. 23, 24, 25 and 26, perpetuated and recorded by Bruce A. Shaner, Registered Land Surveyor No. 430, in 1964, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, from which an original topographic feature:</p> <p style="margin-left: 40px;">The center of the easterly edge of a rock outcrop, 50 x 35 x 9 ft. high, long side bears E. and W., bears N. 89° 34' E., 3.00 chs. dist.</p> <p>and the original bearing objects</p> <p style="margin-left: 40px;">The top center of a rock outcrop, 6 x 5 x 1½ ft. high, bears N. 43° E., 327 lks. dist., no visible marks. (Record, 4 ft. above ground, N. 46° E., 250 lks.)</p> <p style="margin-left: 40px;">The top center of a rock outcrop, 20 x 12 x 8 ft. high, bears S. 46° W., 547 lks. dist., no visible marks. (Record, 5 ft. above ground, S. 45° W., 410 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="4">T 28 S R 5 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 23</td> <td style="padding: 0 5px;">S 24</td> <td colspan="2"></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> <td colspan="2"></td> </tr> <tr> <td colspan="4" style="text-align: center;">1988</td> </tr> </table> </div> <p>from which a new reference monument</p> <p style="margin-left: 40px;">A brass tablet, 3½ ins. diam., with a 3½ in. stem cemented into a drill hole, in the SW. cor. of a rock outcrop, 6 x 4 x 4 ft. high, for a reference monument, bears N. 55° 19' E., 3.038 chs. dist., mkd. RM T28S R5W S24 200.5 FT 1988 and an arrow pointing to the corner.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the iron rod alongside the stainless steel post.</p> <p>The corner is located in a wire fence line, extending E. and W.</p> <p>From this point, United States Coast and Geodetic Survey triangulation station "DODSON," bears N. 14° 02' 00" E., 34.619 chs. dist., monumented with a bronze disk, cemented into solid rock, mkd. DODSON 1942.</p> <p>From this same point, a United States Coast and Geodetic Survey azimuth mark, bears N. 85° 44' E., 2.887 chs. dist., monumented with a bronze disk, 4 ins. diam., cemented into solid rock, mkd. DODSON 1942 and an arrow pointing northerly.</p>	T 28 S R 5 W				S 23	S 24			S 26	S 25			1988			
T 28 S R 5 W																	
S 23	S 24																
S 26	S 25																
1988																	
18.20	Creek, 8 lks. wide, course S. 40° E.; asc. over SE. slope.																
36.70	<p>Spur, slopes S.; desc. over SW. slope.</p> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp. S. 88° 23' 30" W., bet. secs. 24 and 25.</p> <p>Descend over broken SW. slope, through scattering timber and undergrowth.</p>																