

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

18701

CHAINS

39.975 The $\frac{1}{4}$ sec. cor. of secs. 24 and 25, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 28 S R 5 W
 $\frac{1}{4}$ S 24
S 25
1961

from which the original bearing objects

The high point of a rock outcrop, 2 x 2 x $4\frac{1}{2}$ ft. high, bears East, 300 lks. dist., mkd. with an X chiseled into the W. side by Byron.

The top center of a rock outcrop, 9 x 7 x $6\frac{1}{2}$ ft. high, bears S. 33° E., 440 lks. dist., no visible marks.

The corner is located in an old fence line, extending E. and W.

S. $89^\circ 02' 00''$ W., beginning new measurement.

Descend over SW. slope.

12.50 Creek, 5 lks. wide, course S. 10° E.; asc. over SE. slope.

19.20 Spur, slopes S. 60° E.; desc. over SW. slope.

24.70 Creek, 3 lks. wide, course S. 80° E.; asc. over SE. slope.

37.50 The easterly edge of a rock outcrop, 50 x 35 x 9 ft. high, long side bears E. and W.

40.495 The cor. of secs. 23, 24, 25 and 26.

N. $1^\circ 28' 30''$ E., bet. secs. 23 and 24.

Ascend over open SE. slope.

31.00 Spur slopes SW.; desc. over broken, rocky NW. slope, through a recently burned area.

40.200 The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, from original evidence no longer in existence, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 28 S R 5 W
 $\frac{1}{4}$
S 23 | S 24
1961

from which a bearing object set by Byron

A PK nail, in the westerly face of a rock bluff, bears N. $63\frac{1}{2}^\circ$ E., 9 lks. dist., (The nail is 6 ft. above the base of the bluff.)

and a new reference monument

A brass tablet, $3\frac{1}{4}$ ins. diam., with a $3\frac{1}{2}$ in. stem cemented into the high point of a rock outcrop, 12 x 5 x 4 ft. high, bears S. 22° W., 20.9 lks. dist., mkd. RM $\frac{1}{4}$ S23 13.8 FT 1988 and an arrow pointing to the corner.