

County Surveyor's Record, Douglas County, Oregon

18702

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp. N. 0° 48' 00" W., bet. secs. 34 and 35.</p> <p>Ascend over SE. slope, through scattering timber and undergrowth.</p>
4.20	<p>Spur, slopes N. 60° E.; desc. over broken N. slope, through heavy timber and dense undergrowth.</p>
15.70	<p>Creek, 2 lks. wide, course N. 40° E.; asc. over broken S. slope.</p>
20.065	<p>Point for the S 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 1/16 S 34 S 35 1988</p> </div> <p>from which</p> <p style="margin-left: 40px;">A cedar, 14 ins. diam., bears N. 45½° E., 46 lks. dist., mkd. S 1/16 S35 BT.</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears S. 78° W., 99 lks. dist., mkd. S 1/16 S34 BT.</p> <p>Continue over S. slope.</p>
20.70	<p>Spur, slopes N. 55° E.; desc. over NE. slope.</p>
27.20	<p>Creek, 5 lks. wide, course N. 55° E.; asc. over SE. slope.</p>
30.60	<p>Spur, slopes N. 55° E.; desc. over NE. slope.</p>
36.80	<p>Creek, 3 lks. wide, course S. 75° E.; asc. over broken SE. slope.</p>
40.130	<p>The ¼ sec. cor. of secs. 34 and 35, perpetuated and recorded by John M. Markham Jr., Registered Engineer No. 2880, in 1950, monumented with an iron pipe, 1 in. diam., firmly set, projecting 15 ins. above ground, from which the remains of the original bearing trees:</p> <p style="margin-left: 40px;">A root hole, bears N. 50½° E., 79 lks. dist., with a down fir alongside, 50 ins. diam., with scribe mark 1 visible on an opened blaze. (Record, N. 45° E., 82 lks.)</p> <p style="margin-left: 40px;">A rotted fir stump, size indeterminate, bears N. 35¼° W., 22 lks. dist., no marks remaining. (Record, N. 25° W., 19 lks.)</p> <p>and the remains of the bearing trees mkd. by Markham</p> <p style="margin-left: 40px;">A fir, 22 ins. diam., bears N. 77° E., 21 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">An oak snag, 12 ins. diam., bears N. 86½° W., 62 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 S R 5 W ¼ S 34 S 35 1988</p> </div>