

County Surveyor's Record, Douglas County, Oregon

18704

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>and a bearing tree mkd. by Byron</p> <p style="text-align: center;">A fir, 25 ins. diam., bears S. 89° W., 430 lks. dist., with healed blaze.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89° 38' 00" W., bet. secs. 26 and 35.</p> <p>Ascend over broken SE. slope, through heavy timber and dense undergrowth.</p>
28.90	Creek, 10 lks. wide, course S. 60° E.; asc. over steep E. slope.
40.190	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 28 S R 5 W</p> <p>$\frac{1}{4}$ $\frac{S\ 26}{S\ 35}$</p> <p>1988</p> </div> <p>from which</p> <p style="text-align: center;">A fir, 4 ins. diam., bears S. 3½° W., 35 lks. dist., mkd. X BT.</p> <p style="text-align: center;">A fir, 6 ins. diam., bears N. 73¾° W., 31 lks. dist., mkd. $\frac{1}{4}$ S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, a point of unknown origin, bears S. 42° 05' E., 1.42 chs. dist., monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 24 ins. above ground.</p> <p>Ascend over a broken NE. slope.</p>
50.40	Spur, slopes N. 20° E.; cross over broken N. slope.
58.80	Ravine, drains N. 20° W.; asc. over NE. slope.
60.285	<p>Point for the W 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16 $\frac{S\ 26}{S\ 35}$</p> <p>1988</p> </div> <p>from which</p> <p style="text-align: center;">A fir, 15 ins. diam., bears S. 60° W., 55 lks. dist., mkd. W 1/16 S35 BT.</p> <p style="text-align: center;">A fir, 4 ins. diam., bears N. 58½° W., 69 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Continue over NE. slope.</p>