

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

18705

CHAINS	
68.10	Ridge, bears N. 10° E. and S. 20° E.; desc. over NW. slope, through open pastureland.
70.80	Dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.
80.380	The cor. of secs. 26, 27, 34 and 35.
N. 0° 08' 00" W., bet. secs. 26 and 27.	
Descend over NW. slope, through open pastureland.	
1.20	Creek, 2 lks. wide, course N. 65° W.; asc. over SW. slope.
3.60	Dirt road, 15 lks. wide, bears NE. and SW.
6.70	Spur, slopes W.; desc. over broken NW. slope.
19.10	Creek, 2 lks. wide, course W.; asc. over SW. slope.
19.590	Point for the S 1/16 sec. cor. of secs. 26 and 27.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.	
<div style="display: flex; justify-content: center; align-items: center; gap: 10px;"> <div style="text-align: center;">S 1/16</div> <div style="text-align: center;">S 27 S 26</div> </div> <div style="text-align: center;">1988</div>	
from which	
The chisel mark X on the high point of a rock outcrop, 9 x 7 x 6½ ft. high, bears N. 49° E., 90 lks. dist.	
A cedar, 15 ins. diam., bears S. 80¼° W., 123 lks. dist., mkd. S 1/16 S27 BT.	
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.	
Continue over SW. slope.	
27.70	Top of ascent, slopes W.; cross W. slope.
29.10	Wire fence, bears N. 15° E. and S. 30° W.
34.20	Begin descent over NE. slope, through heavy timber and dense undergrowth.
39.180	Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
<div style="display: flex; justify-content: center; align-items: center; gap: 10px;"> <div style="text-align: center;">T 28 S R 5 W</div> <div style="text-align: center;">¼</div> <div style="text-align: center;">S 27 S 26</div> </div> <div style="text-align: center;">1988</div>	
from which	
A fir, 10 ins. diam., bears N. 54¼° E., 23 lks. dist., mkd. ¼ S26 BT.	
A fir, 14 ins. diam., bears N. 33° W., 55 lks. dist., mkd. ¼ S27 BT.	
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.	