

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 5 W., Willamette Meridian, Oregon

18707

CHAINS	
	Continue over W. slope.
46.40	Creek, 3 lks. wide, course NW.; asc. over NE. slope.
48.10	Spur, slopes NW.; desc. over broken SW. slope.
58.30	Creek, 5 lks. wide, course N. 30° W.; asc. over NE. slope.
66.20	Dirt road, 15 lks. wide, bears N. 60° W. and S. 60° W.
76.80	Spur, slopes N.; desc. over broken NW. slope.
78.890	The cor. of secs. 22, 23, 26 and 27.
N. 2° 00' 30" E., bet. secs. 22 and 23.	
Descend over broken NW. slope, through scattering timber and dense undergrowth.	
5.40	Spur, slopes N. 40° W.; continue to descend.
13.90	Creek, 15 lks. wide, course W.; asc. over SW. slope.
19.30	Spur, slopes S. 50° W.; desc. over broken NW. slope.
28.80	Graveled road, 15 lks. wide, bears N. 70° W. and S. 70° E.
40.675	The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1938, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1959, monumented with a sandstone, 20 x 14 x 10 ins., firmly set, 12 ins. in the ground, mkd. $\frac{1}{4}$ S on W. face, from which the remains of the original bearing trees: <div style="margin-left: 40px;"> <p>A madrone, 30 ins. diam., bears N. 58° E., 32 lks. dist., no marks visible on an open, rotted blaze. (Record, N. 50° E., 23 lks.)</p> <p>A fir stump, 39 ins. diam., bears S. 58° W., 35 lks. dist., no visible marks. (Record, S. 60° W.)</p> <p>and bearing trees mkd. by Byron</p> <p>A fir, 14 ins. diam., bears N. 52° E., 28 lks. dist., with healed blaze.</p> <p>A fir, 19 ins. diam., bears N. 82<math>\frac{1}{2}</math>° W., 81 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 S R 5 W</p> <p><math>\frac{1}{4}</math></p> <p>S 22   S 23</p> <p>1988</p> </div> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> </div>
From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.	
N. 0° 03' 30" E., bet. secs. 33 and 34.	
Ascend over open SW. slope.	