

County Surveyor's Record, Douglas County, Oregon

18708

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
4.30	Spur, slopes W.; desc. over broken N. slope, through scattering timber and dense undergrowth.
38.90	Creek, 8 lks. wide, course N. 20° W.; asc. over broken SW. slope.
40.130	<p>The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, determined from the remains of an original bearing tree:</p> <p style="margin-left: 40px;">A sawed fir stump, 28 ins. diam., bears S. 83$\frac{3}{4}$° W., 186 lks. dist., with axe marks and a chaining notch on an open blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 S R 5 W</p> <p>$\frac{1}{4}$</p> <p>S 33 S 34</p> <p>1988</p> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears S. 75$\frac{1}{2}$° E., 55 lks. dist., mkd. $\frac{1}{4}$ S34 BT.</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears S. 75$\frac{1}{4}$° W., 82 lks. dist., mkd. $\frac{1}{4}$ S33 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 05' 00" W., beginning new measurement.</p> <p>Ascend over broken SW. slope.</p>
11.80	Spur, slopes S. 75° W.; desc. over NW. slope.
25.10	Creek, 10 lks. wide, course W.; asc. over SW. slope.
26.10	Creek, 1 lk. wide, course S. 50° W.; continue to ascend.
31.10	Spur, slopes W.; desc. over NW. slope.
31.20	A point of unknown origin, monumented with an iron rod, $\frac{1}{2}$ in. diam., firmly set, projecting 6 ins. above ground, with a steel fence post alongside.
40.085	<p>The cor. of secs. 27, 28, 33, and 34, perpetuated and recorded by W. F. Briggs, County Surveyor, in 1893, and further perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1950, monumented with an iron pipe, 1$\frac{1}{4}$ ins. diam., firmly set, projecting 8 ins. above the ground, from which the remains of an original bearing tree:</p> <p style="margin-left: 40px;">A root hole, bears S. 30° W., 38 lks. dist., with a down and rotted oak alongside, size indeterminate, with axe marks visible on rotted blaze.</p> <p>and bearing trees mkd. by Briggs</p> <p style="margin-left: 40px;">An oak, 34 ins. diam., bears S. 51° E., 153 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">An oak, 12 ins. diam., bears N. 59° W., 60$\frac{1}{2}$ lks. dist., with a partially healed over rotted blaze.</p> <p>and bearing trees mkd. by Markham</p>