

# County Surveyor's Record, Douglas County, Oregon

18710      Dependent Resurvey of a Portion of the Subdivisional Lines,  
 T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">An oak, 7 ins. diam., bears S. 18½° E., 57 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 15° W., 46 lks. dist., mkd. W 1/16 S34 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Continue over broken W. slope.</p>
80.260	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr style="width: 80%; margin-left: 0;"/> <p>N. 0° 02' 30" W., bet. secs. 27 and 28.</p> <p>Descend over NW. slope, through scattering timber and patches of dense undergrowth.</p>
0.55	Creek, 2 lks. wide, course N. 70° W.; asc. over broken SW. slope.
6.20	Spur, slopes S. 80° W.; desc. over broken NW. slope.
8.80	Creek, 3 lks. wide, course S. 50° W.; asc. over SW. slope.
17.70	Spur, slopes S. 50° W.; desc. over NW. slope.
20.080	<p>Point for the S 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>S 1/16</p> <p>S 28   S 27</p> <p>1988</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 54¼° E., 16 lks. dist., mkd. S 1/16 S27 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 80¼° W., 11 lks. dist., mkd. S 1/16 S28 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is 10 lks. W. of a N. and S. wire fence line.</p> <p>Continue over NW slope.</p>
23.80	Asphalt road, 35 lks. wide, bears N. 20° E. and S. 20° W.
32.50	Ravine, drains W.; asc. over SW. slope.
33.30	Graveled road, 15 lks. wide, bears N. 30° W. and S. 30° E.
39.50	Spur, slopes W.; desc. over NW. slope.
40.160	<p>Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 28 S R 5 W</p> <p>¼</p> <p>S 28   S 27</p> <p>1988</p> </div>