

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 5 W., Willamette Meridian, Oregon

18711

CHAINS					
	<p>from which</p> <p style="padding-left: 40px;">An oak, 17 ins. diam., bears S. 35½° E., 43 lks. dist., mkd. ¼ S27 BT.</p> <p style="padding-left: 40px;">An oak, 7 ins. diam., bears S. 61¼° W., 19 lks. dist., mkd. ¼ S28 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Continue over NW. slope.</p>				
44.10	Graveled road, 15 lks. wide, bears N. 65° E. and S. 65° W.				
45.60	Ravine, drains N. 65° W.; asc. over SW. slope.				
52.10	Spur, slopes W.; desc. over broken NW. slope.				
76.15	Graveled road, 15 lks. wide, bears N. 80° W. and S. 80° E.				
77.80	Roberts Creek, 10 lks. wide, course S. 80° W.; asc. over SW. slope.				
80.320	<p>The cor. of secs. 21, 22, 27 and 28, perpetuated and recorded by H.L. Eppstein, Deputy County Surveyor, in 1921, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1961, monumented with an iron pipe, ¾ in. diam., firmly set, projecting 2 ins. above ground, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A rotted oak stump, size indeterminate, bears N. 16¼° E., 284 lks. dist., no marks remaining. (Record, 288 lks.)</p> <p style="padding-left: 40px;">An ash, 35 ins. diam., bears S. 31½° E., 287 lks. dist., no visible marks. (Record, S. 30½° E., 292 lks.)</p> <p style="padding-left: 40px;">A maple, 59 ins. diam., bears S. 8¼° W., 240 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Eppstein</p> <p style="padding-left: 40px;">A maple, 26 ins. diam., bears S. 10° E., 273 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A maple, 18 ins. diam., bears N. 52° E., 78 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A maple, 22 ins. diam., bears N. 11° W., 112 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 S R 5 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> </table> <p>1988</p> </div> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located at the intersection of wire fences, extending N., S. and W.</p>	S 21	S 22	S 28	S 27
S 21	S 22				
S 28	S 27				
	<hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p>				