

County Surveyor's Record, Douglas County, Oregon

18712

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	N. 87° 00' 00" W., bet. secs. 22 and 27.
	Descend over broken NW. slope, through scattering timber and dense undergrowth.
10.20	Dirt road, 15 lks. wide, bears N. 5° W. and S. 5° E.
10.90	Creek, 5 lks. wide, course N. 20° E.; asc. over broken NE. slope.
24.10	Spur, slopes N. 10° W.; desc. over W. slope.
40.110	The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, determined at record bearing and distance, from the remains of an original bearing tree: <p style="margin-left: 40px;">A sawed oak stump, 18 ins. diam., bears S. 61$\frac{1}{4}$° E., 138 lks. dist., with axe marks visible on a rotted blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. dia., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 S R 5W</p> <p>$\frac{1}{4}$ $\frac{S}{S}$ $\frac{22}{27}$</p> <p>1988</p> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears S. 5° E., 20 lks. dist., mkd. $\frac{1}{4}$ S27 BT.</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears N. 44$\frac{1}{2}$° W., 60 lks. dist., mkd. $\frac{1}{4}$ S22 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on a NW. slope, 25 lks. S. of a creek, 4 lks. wide, course N. 80° W., and 60 lks. N. of a wire fence line, extending E. and W.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 89° 58' 00" W., beginning new measurement.</p> <p>Descend over broken W. slope.</p>
6.50	Creek, 5 lks. wide, course S. 60° W.; asc. over broken SE. slope.
40.100	The cor. of secs. 21, 22, 27 and 28.
<hr/> <p>Subdivision of Section 25 T. 28 S., R. 5 W., Willamette Meridian, Oregon</p> <hr/>	
	From the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.
	N. 0° 13' 30" E., on the N. and S. center line of sec. 25.
	Descend over steep, broken NE. slope, through heavy timber and light undergrowth.
8.00	Bilger Creek, 5 lks. wide, course S. 20° E.; asc. over SW. slope.
19.800	Point for the center S 1/16 sec. cor. of sec. 25.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$ ft. base, to top, with brass cap mkd.