

# County Surveyor's Record, Douglas County, Oregon

18714

Subdivision of Section 25,  
T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears N. 55½° E., 150 lks. dist., mkd. CN 1/16 S25 BT.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 12° W., 33 lks. dist., mkd. CN 1/16 S25 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on a steep, open rocky SW. slope.</p> <p>Ascend over broken SW. slope, through scattered timber and pastureland.</p>
79.420	<p>The ¼ sec. cor. of secs. 24 and 25</p> <hr style="width: 80%; margin-left: 0;"/> <p>From the ¼ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp. S. 88° 47' 00" W., on the E. and W. center line of sec. 25.</p> <p>Ascend over broken NE. slope, through burnt timber.</p>
22.65	<p>Ridge, bears N. 50° W. and S. 50° E.; desc. over steep, broken SW. slope.</p>
29.70	<p>Ravine, drains S. 10° W.; asc. over SE. slope.</p>
35.85	<p>Spur, slopes S. 55° W.; desc. over steep, rocky NW. bluffs.</p>
40.350	<p>The true point for the center ¼ sec. cor. of sec. 25.</p> <p>Descend over steep NW. slope.</p>
46.10	<p>Bilger Creek, 5 lks. wide, course SW.; asc. over broken SE. slope.</p>
48.60	<p>Spur, slopes S.; desc. over SW. slope.</p>
49.20	<p>Creek, 5 lks. wide, course S. 50° E.; asc. over broken SE. slope.</p>
60.410	<p>Point for the center W 1/16 sec. cor. of sec. 25</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C    <math>\frac{W \ 1/16}{S \ 25}</math>    C</p> <p>1988</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 51° E., 92 lks. dist., mkd. CW 1/16 S25 BT.</p> <p style="padding-left: 40px;">A fir, 49 ins. diam., bears S. 42° W., 166 lks. dist., mkd. CW 1/16 S25 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend over SE. slope.</p>
71.20	<p>Spur, slopes SE.; desc. over broken SW. slope.</p>
80.470	<p>The ¼ sec. cor. of secs. 25 and 26.</p> <p>From the N 1/16 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p>