

County Surveyor's Record, Douglas County, Oregon

18716

Subdivision of Section 25,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	From the center S 1/16 sec. cor. of sec. 25.
	S. 88° 54' 00" W., on the E. and W. center line of the SW¼ of sec. 25.
	Descend over steep SW. slope, through heavy timber and light undergrowth.
3.30	Bilger Creek, 5 lks. wide, course S. 20° E.; asc. over broken NE. slope.
19.920	The SW 1/16 sec. cor. of sec. 25.

	S. 88° 48' 00" W., beginning new measurement.
	Ascend over NE. slope.
0.50	Ridge, bears N. 5° W. and S. 20° E.; desc. over broken SW. slope.
10.20	Woven wire fence, bears N. 55° W. and S. 55° E.
16.55	Creek, 2 lks. wide, course S. 20° E.; asc. over gentle SE. slope.
19.15	Woven wire fence, bears N. 20° E. and S. 20° W.
19.925	The S 1/16 sec. cor. of secs. 25 and 26.

	From the center N 1/16 sec. cor. of sec. 25.
	S. 88° 53' 30" W., on the E. and W. center line of the NW¼ of sec. 25.
	Descend over SW. slope, through open pasture.
4.00	Bilger Creek, 10 lks. wide, course S. 50° E.; asc. over NE. slope.
8.30	Spur, slopes S. 20° E.; desc. over SW. slope.
11.95	Creek, 5 lks. wide, course S. 15° E.; asc. over SE. slope.
19.10	Spur, slopes S. 25° E.; desc. over SW. slope.
23.65	Creek, 2 lks. wide, course S. 40° E.; asc. over NE. slope.
34.05	Spur, slopes S. 50° E.; desc. over SW. slope.
40.310	The N 1/16 sec. cor. of secs. 25 and 26

	Subdivision of Section 26 T. 28 S., R. 5 W., Willamette Meridian, Oregon

	From the ¼ sec. cor. of secs. 26 and 35.
	N. 0° 18' 00" W., on the N. and S. center line of sec. 26.
	Descend over NE. slope, through heavy timber and dense undergrowth.
8.20	Creek, 2 lks. wide, course S. 55° E.; asc. over broken SE. slope.
19.680	Point for the center S 1/16 sec. cor. of sec. 26.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C S 1/16 S 26 C 1988