

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 26,  
T. 28 S., R. 5 W., Willamette Meridian, Oregon

18717

| CHAINS |   |
|--------|---|
|        | <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 78° E., 21 lks. dist.,<br/>mkd. CS 1/16 S26 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 65° W., 26 lks. dist.,<br/>mkd. CS 1/16 S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend over broken SE. slope, through scattered timber and light undergrowth.</p>         |
| 39.360 | <p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 26, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 28 S R 5 W<br/>C<math>\frac{1}{4}</math> S 26<br/>1988 ✓</p>                                       |
|        | <p>from which</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears S. 40<math>\frac{1}{2}</math>° E., 100 lks. dist.,<br/>mkd. X BT.</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears S. 4<math>\frac{1}{4}</math>° W., 121 lks. dist.,<br/>mkd. C<math>\frac{1}{4}</math> S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend over SE. slope.</p> |
| 39.45  | Ridge, bears N. 65° E. and S. 80° W.; desc. over broken NW. slope.  |
| 40.15  | Dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W.  |
| 60.95  | Ravine, drains N. 70° W.; asc. over SW. slope.  |
| 68.25  | Spur, slopes N. 65° E.; desc. over NW. slope.   |
| 76.10  | Dry creekbed, drains N. 20° W.; asc. over SW. slope.  |
| 78.930 | The $\frac{1}{4}$ sec. cor. of secs. 23 and 26.   |
|        | <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 25 and 26.</p> <p>S. 89° 22' 00" W., on the E. and W. center line of sec. 26.</p> <p>Ascend over broken SE. slope, through open pastures and scattered timber.</p>  |
| 39.960 | The center $\frac{1}{4}$ sec. cor. of sec. 26.  |
|        | Ascend over SE. slope.  |
| 47.10  | Ridge, bears N. 60° E. and S. 60° W.; desc. over W. slope.  |
| 59.10  | Ravine, drains N. 30° W.; asc. over NE. slope.  |
| 59.990 | Point for the center W 1/16 sec. cor. of sec. 26.   |
|        | Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  |