

County Surveyor's Record, Douglas County, Oregon

18718

Subdivision of Section 26,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

C W 1/16 C
 S 26
 1988

from which

A fir, 20 ins. diam., bears S. 16° E., 377 lks. dist.,
mkd. CW 1/16 S26 BT.

An oak, 11 ins. diam., bears N. 77° W., 116 lks dist.,
mkd. CW 1/16 S26 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

The corner is located on a grassy, open NE. slope.

Ascend over NE. slope.

61.20 Spur, slopes N. 50° W.; desc. over broken NW. slope.

80.020 The ¼ sec. cor. of secs. 26 and 27.

From the W 1/16 sec. cor. of secs. 26 and 35.

N. 0° 13' 00" W., on the N. and S. center line of the SW¼ of sec. 26.

Descend over NE. slope, through heavy timber and dense undergrowth.

4.80 Ravine, drains N. 60° E.; asc. over SE. slope.

6.65 Spur, slopes S. 70° E.; continue ascent over broken NE. slope.

19.635 Point for the SW 1/16 sec. cor. of sec. 26, at intersection with the E. and W. center line of the SW¼.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

SW 1/16 S 26
1988

from which

A fir, 12 ins. diam., bears N. 56° E., 79 lks. dist.,
mkd. SW 1/16 S26 BT.

An oak, 14 ins. diam., bears S. 58° E., 64 lks. dist.,
SW 1/16 S26 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Ascend over NE. slope, through open pasture.

24.95 Dirt road, 15 lks. wide, bears N. 50° E. and S. 30° W.

29.20 Ridge, bears N. 40° E. and S. 40° W.; desc. over NW slope.

39.265 The center W 1/16 sec. cor. of sec. 26.

From the center S 1/16 sec. cor. of sec. 26.

S. 89° 27' 00" W., on the E. and W. center line of the SW¼ of sec. 26.

Ascend over SE. slope, through heavy timber and dense undergrowth.