

County Surveyor's Record, Douglas County, Oregon

18720

Subdivision of Section 27,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	T 28 S R 5 W C $\frac{1}{4}$ S 27 1988
	from which A fir, 12 ins. diam., bears S. 3° W., 22 lks. dist., mkd. C $\frac{1}{4}$ S27 BT. A fir, 10 ins. diam., bears N. 8° W., 32 lks. dist., mkd. C $\frac{1}{4}$ S27 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Ascend over steep SE. slope.
42.60	Spur, slopes W.; desc. over broken NW. slope.
58.60	Creek, 3 lks. wide, course N. 60° W.; continue descent over NW. slope.
61.45	Woven wire fence, bears E. and W.
63.90	Ravine, drains N. 35° W.; asc. over SW. slope.
75.65	Spur, slopes W.; desc. over NW. slope.
80.400	The $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	<hr/> From the $\frac{1}{4}$ sec. cor. of secs. 26 and 27. N. 89° 11' 30" W., on the E. and W. center line of sec. 27. Ascend over NE. slope, through heavy timber and light undergrowth.
3.80	Spur, slopes N. 35° W.; desc. over SW. slope.
38.85	Ravine, drains S. 20° W.; asc. over SE. slope.
40.100	The center $\frac{1}{4}$ sec. cor. of sec. 27. Ascend over SE. slope.
40.35	Spur, slopes S. 10° W.; desc. over broken SW. slope.
58.95	Roberts Creek, 10 lks. wide, course NW.; asc. over steep NE. slope.
60.165	Point for the center W 1/16 sec. cor. of sec. 27. Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	C $\frac{W\ 1/16}{S\ 27}$ C 1988
	from which A fir, 7 ins. diam., bears S. 70° E., 46 lks. dist., mkd. CW 1/16 S27 BT. A fir, 9 ins. diam., bears N. 11° W., 15 lks. dist., mkd. CW 1/16 S27 BT.