

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 27,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

18721

CHAINS	
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Ascend over steep, rocky NE. slope.
66.50	Dirt road, 15 lks. wide, bears N. 10° W. and S. 25° E.
71.35	Spur, slopes N.; desc. over SW. slope.
74.70	Graveled road, 30 lks. wide, bears N. 20° W. and S. 20° E.
80.230	The $\frac{1}{4}$ sec. cor. of secs. 27 and 28.

	From the S $\frac{1}{16}$ sec. cor. of secs. 26 and 27.
	N. 89° 33' 00" W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 27.
	Descend over broken SW. slope, through heavy timber and dense undergrowth.
33.40	Roberts Creek, 8 lks. wide, course N. 25° W.; desc. over NW. slope.
40.110	The center S $\frac{1}{16}$ sec. cor. of sec. 27.

	From the W $\frac{1}{16}$ sec. cor. of secs. 27 and 34.
	N. 0° 03' 00" W., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 27.
	Ascend over SW. slope, through open pasture and scattered timber.
12.00	Spur, slopes N. 35° W.; desc. over NE. slope.
19.960	Point for the SW $\frac{1}{16}$ sec. cor. of sec. 27, at intersection with the E. and W. center line of the SW $\frac{1}{4}$.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	SW $\frac{1}{16}$ S 27 1988
	from which
	A fir, 8 ins. diam., bears S. 9° E., 24 $\frac{1}{2}$ lks. dist., mkd. SW $\frac{1}{16}$ S27 BT.
	A fir, 9 ins. diam., bears S. 58° W., 30 lks. dist., mkd. SW $\frac{1}{16}$ S27 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	The corner is located on a NE. slope, 2 lks. S. of a woven wire fence, bearing E. and W.
	Descend over NE. slope.
27.65	Graveled road, 30 lks. wide, bears S. 20° E. and N. 25° W.
39.920	The center W $\frac{1}{16}$ sec. cor. of sec. 27.

	From the center S $\frac{1}{16}$ sec. cor. of sec. 27.