

# County Surveyor's Record, Douglas County, Oregon

18722

Subdivision of Section 27,  
T. 28 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	N. 89° 33' 30" W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 27.
	Descend over broken NW. slope, through heavy timber and dense undergrowth.
5.60	Ravine, drains N. 25° E.; asc. over SE. slope.
10.55	Spur, slopes N. 25° E.; desc. over NW. slope.
14.50	Ravine, drains N. 10° E.; asc. over NE. slope.
17.70	Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.
20.070	The SW 1/16 sec. cor. of sec. 27.
	Ascend over NE. slope.
22.45	Spur, slopes N.; desc. over broken NW. slope.
40.140	The S 1/16 sec. cor. of secs. 27 and 28
<hr/> Subdivision of Section 34, T. 28 S., R. 5 W., Willamette Meridian, Oregon <hr/>	
	From the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp. N. 0° 06' 30" W., on the N. and S. center line of sec. 34.
	Ascend over broken S. slope, through scattered timber and light undergrowth.
6.10	Spur, slopes W.; desc. over NW. slope.
7.25	Dirt road, 20 lks. wide, bears NE. and SW.
20.025	Point for the center S 1/16 sec. cor. of sec. 34.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	C S 1/16   S 34 C 1988
	from which
	A white oak, 14 ins. diam., bears N. 67° E., 224 lks. dist., mkd. CS 1/16 S34 BT.
	A fir, 25 ins. diam., bears S. 43° E., 151 lks. dist., mkd. CS 1/16 S34 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Descend over broken NW. slope.
40.050	Point for the center $\frac{1}{4}$ sec. cor. of sec. 34, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 28 S R 5 W C $\frac{1}{4}$ S 34 1988