

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 35,
T. 28 S., R. 5 W., Willamette Meridian, Oregon

18725

CHAINS	
	From the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp. N. $0^{\circ} 15' 30''$ E., on the N. and S. center line of sec. 35.
	Ascend along E. slope, through heavy timber and dense undergrowth.
4.60	Spur, slopes N. 60° E.; desc. over NE. slope.
7.75	Creek, 5 lks. wide, course N. 75° E.; asc. over SE. slope.
13.05	Gravel road, 20 lks. wide, bears N. 40° E. and S. 40° W.
15.70	Spur, slopes N. 50° E.; desc. over NE. slope.
18.70	Gravel road, 20 lks. wide, bears N. 70° E. and S. 65° W.
23.65	Creek, 5 lks. wide, course N. 65° E.; asc. over SE. slope.
33.25	Gravel road, 20 lks. wide, bears N. 50° E. and S. 25° W.
39.850	Point for the center $\frac{1}{4}$ sec. cor. of sec. 35, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 28 S R 5 W C $\frac{1}{4}$ S 35 1988
	from which
	A fir, 11 ins. diam., bears N. 71° E., 29 lks. dist., mkd. C $\frac{1}{4}$ S35 BT.
	A fir, 5 ins. diam., bears S. 36° W., 33 lks. dist., mkd. X BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Ascend over SE. slope.
41.35	Spur, slopes S. 70° E.; desc. over NE. slope.
43.50	Creek, 1 lk. wide, course S. 75° E.; asc. over SE. slope.
48.50	Spur, slopes S. 70° E.; desc. over NE. slope.
52.50	Ravine, drains S. 40° E.; asc. over SW. slope.
59.560	Point for the center N $\frac{1}{16}$ sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C N $\frac{1}{16}$ S 35 C 1988
	from which
	A fir, 27 ins. diam., bears N. $80\frac{1}{4}^{\circ}$ E., $50\frac{1}{2}$ lks. dist., mkd. CN $\frac{1}{16}$ S35 BT.
	A cedar, 10 ins. diam., bears N. $14\frac{1}{2}^{\circ}$ W., 16 lks. dist., mkd. CN $\frac{1}{16}$ S35 BT.