

County Surveyor's Record, Douglas County, Oregon

18731

Subdivision of Section 13,
T. 23 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
12.90	Leave timber, edge bears generally N. 55° W. and S. 55° E.
13.00	Dirt road, 18 lks. wide, bears N. 55° W. and S. 55° E.
15.30	Lake Creek, 53 lks. wide, course N. 35° W.; enter open pastureland.
27.15	Mill Creek County Road, asphalt surface, 48 lks. wide, bears N. 50° W. and S. 50° E.; asc. S. slope across cultivated land, through scattering timber.
39.270	Point for the center $\frac{1}{4}$ sec. cor. of sec. 13, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 23 S R 10 W C$\frac{1}{4}$ S 13 1988 </div>
	from which A fir, 13 ins. diam., bears N. 47 $\frac{1}{4}$ ° E., 37 lks. dist., mkd. C $\frac{1}{4}$ S13 BT. A fir, 7 ins. diam., bears S. 75 $\frac{1}{4}$ ° E., 47 lks. dist., mkd. C $\frac{1}{4}$ S13 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Ascend over SW. slope, through moderate timber and dense undergrowth.
45.14	Spur, slopes S. 85° W.; desc. over NW. slope.
53.30	Ravine, drains W.; asc. over SW. slope.
56.30	Spur, slopes W.; desc. over NW. slope.
77.80	Mill Creek County Road, asphalt surface, 48 lks. wide, bears N. 30° E. and S. 10° W., in a curve.
78.020	The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. <div style="text-align: center;"> T 23 S $\frac{1}{4}$ $\frac{S\ 12}{S\ 13}$ $\frac{R\ 10}{W}$ 1964 </div>
	from which the remains of an original bearing tree A sawed fir stump, 48 ins. diam., bears N. 70° W., 30 lks. dist., no marks visible. and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1964. A fir, 11 ins. diam., bears S. 75 $\frac{1}{2}$ ° W., 93 lks. dist., with healed blaze. A maple, 11 ins. diam., bears N. 77 $\frac{1}{2}$ ° W., 38 lks. dist. with healed blaze. From this point, the United States Geological Survey triangulation station "HIGH POLE 1953", bears N. 32° 30' 26" E., 325.230 chs. dist., monumented with a standard brass tablet, 3 $\frac{1}{2}$ ins. diam., set in an iron post, 4 ins. diam., firmly set, projecting 6 ins. above