

County Surveyor's Record, Douglas County, Oregon

18732

Subdivision of Section 13,
T. 23 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

ground, mkd. HIGH POLE 1953.

From the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 23 S
R 10 W R 9 W
 $\frac{1}{4}$
S 13 | S 18
1967

from which bearing trees mkd. by Beck

A fir, 28 ins. diam., bears N. 38° E., 66 lks. dist., with healed blaze.

A hemlock, 29 ins. diam., bears N. 38° W., 55 lks. dist. with healed blaze.

N. 89° 08' 00" W., on the E. and W. center line of sec. 13.

Descend over SW. slope, through heavy timber and dense undergrowth.

3.35 Ravine, drains S. 30° W.; asc. over SE. slope.

5.90 Spur, slopes S. 20° W.; desc. over SW. slope.

39.680 The center $\frac{1}{4}$ sec. cor. of sec. 13.

Descend over SW. slope, through heavy timber and dense undergrowth.

43.80 Leave timber, edge bears generally N. 10° E. and S. 30° W.

44.05 Mill Creek County Road, asphalt surface, 48 lks. wide, bears N. 10° E. and S. 30° W., in a curve; enter open pastureland.

48.30 Lake Creek, 30 lks. wide, course N.; asc. over E. slope.

69.50 Enter scattering timber, edge bears generally N. and S.; asc. over NE. slope.

79.430 The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.

T 23 S R 10 W
 $\frac{1}{4}$
S 14 | S 13
1958

from which the bearing tree mkd. during the survey of Elliott State Forest, in 1933

A hemlock, 43 ins. diam., bears S. 65° E., 33 lks. dist., with healed blaze.

and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1958

A hemlock, 20 ins. diam., bears N. 24° W., 31 lks. dist., with illegible scribe marks visible on partially healed blaze. (Record, N. 26 $\frac{1}{2}$ ° W.)