

County Surveyor's Record, Douglas County, Oregon

18736

Dependent Resurvey of a Portion of the East Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 29 S	
S 25	
S 36	
R 8 W	
1924	

from which the remains of bearing trees mkd. by Mensch

A root hole, bears S. 42° W., 83 lks. dist., with a down, decayed fir alongside, size indeterminate, no marks visible.

A root hole, bears N. 59° W., 164 lks. dist., with a down fir alongside, 45 ins. diam., with healed blaze.

and the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1962

A grand fir snag, 10 ins. diam., bears S. 25° W., 10 lks. dist., with healed double blaze.

A cedar, 13 ins. diam., bears N. 40° W., 49 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

No suitable tree available in sec. 36.

The corner is located in a timber corner, with timber on NW. and clearcut to NE., SE., and SW.

N. 0° 16' 00" W., on the E. bdy. of sec. 25, marking and blazing the true line.

Descend over NE. slope, through moderate timber and dense under growth.

- 2.55 Ravine, drains N. 40° W.; desc. over NE. slope.
- 4.20 Ravine, drains N. 75° W.; asc. over broken SW. slope.
- 15.95 Spur, slopes N. 70° W.; desc. over broken NW. slope.
- 30.40 Ravine, drains N. 30° E.; asc. over SE. slope.
- 34.810 The cor. of secs. 30 and 31, T. 29 S., R. 7 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 29 S	
S 30	
S 31	
R 7 W	
1924	

from which bearing trees mkd. by Mensch

A grand fir, 15 ins. diam., bears N. 40° E., 36 lks. dist., with healed blaze.

A fir, 18 ins. diam., bears S. 19° E., 51 lks. dist., with healed blaze.

N. 0° 47' 30" W., beginning new measurement.

Ascend over SE. slope.

- 4.00 Spur, slopes E.; desc. over NE. slope.