

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

18739

## CHAINS

A cedar, 16 ins. diam., bears N. 6° E., 6 lks. dist.,  
with healed blaze. (Record, 7 lks.)

A cedar, 17 ins. diam., bears S. 8° W., 26 lks. dist.,  
with healed blaze.

From this point, the  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, used as a  
horizontal control station by the Douglas County Surveyors Office,  
bears N. 0° 10' 29" E., 159.660 chs. dist., monumented with an  
iron post, 1 in. diam., firmly set, projecting 12 ins. above  
ground, with brass cap mkd.  $\frac{1}{4}$  S12 S13 1924, from which the  
original bearing trees:

A white oak, 42 ins. diam., bears N. 30° E., 103 lks.  
dist., with healed blaze.

A white oak, 15 ins. diam., bears S. 64° E., 86 lks.  
dist., with healed blaze.

and bearing trees mkd. by Mensch

A white oak, 19 ins. diam., bears N. 11 $\frac{1}{2}$ ° E., 52 lks.  
dist., with healed blaze.

A white oak, 21 ins. diam., bears S. 83° E., 37 lks.  
dist., remarked by John M. Powell, Deputy County  
Surveyor, in 1966, mkd. with two healed blazes.

---

Dependent Resurvey of a Portion of  
the Boundaries of Tracts 54 and 55,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

---

(Restoring the survey by Fred Mensch in 1924)

From Cor. No. 2 of Tract 54, identical with Cor. No. 3 of Tract  
53, T. 29 S., R. 7 W., determined at record bearing and distance  
from the remains of an original bearing tree:

A sawed cedar stump, 24 ins. diam., bears N. 25° E., 25 lks.  
dist., with scribe marks TR 53 BT visible on open blaze.

and bearing trees mkd. by persons unknown

An oak, 12 ins. diam., bears N. 43° E., 62 lks. dist.,  
with healed double blaze.

A fir, 28 ins. diam., bears S. 15° E., 184 lks. dist.,  
with healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 10 ins.  
in the ground to bedrock, directly over the mark X, and supported  
in a mound of stone, 4 ft. base to top, with brass cap mkd.

TR 53  
AP 3  
TR 54  
1989

Deposit white "DEEP-1" magnetic marker at base of stainless steel  
post.

S. 1° 17' 00" W., on line 2-3 of Tract 54.

Descend over SE. slope, through heavy timber and dense  
undergrowth.