

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the East Boundary,
T. 30 S., R. 10 W., Willamette Meridian, Oregon

18745

CHAINS

above ground, alongside of which is the original sandstone, 14 x 14 x 10 ins., with $\frac{1}{4}$ visible on W. face, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S	
R	S 18
$\frac{1}{4}$ 10	
	R
	9
S 13	W
1965	

from which the remains of the original bearing trees

A sawed fir stump, 25 ins. diam., bears
N.26 $\frac{1}{2}$ °W., 52 $\frac{1}{4}$ lks. dist., with fragmentary
scribe marks visible on opened blaze.

and the remains of the bearing trees mkd. by Powell

A fir, 12 ins. diam., bears S.84°E., 12 $\frac{1}{2}$ lks.
dist., with healed blaze.

A fir stub, size indeterminate, bears N.5°W., 64 lks.
dist., no marks remaining.

and a new bearing tree

A fir, 15 ins. diam., bears S.15°W., 130 lks.
dist., mkd. $\frac{1}{4}$ S13 BT.

Deposit original stone alongside the iron post.

N. 0° 10' W., bet. secs. 13 and 18, marking and blazing the true line.

Descend over NW. slope, through scattering timber and moderate undergrowth.

4.05 Spur, slopes N.40°W.; desc. over NE. slope, changing to NW. slope; also, leave timber and enter logged area.

7.30 Dirt road, 20 lks wide, bears N.50°W. and S.80°E.

20.11 The N 1/16 sec. cor. of secs. 13 and 18, established by Larry LaFlamme for the Georgia Pacific Corp., in 1979, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of the bearing trees mkd. by LaFlamme:

A sawed cedar stump, 45 ins. diam., bears N.27°E.,
30 lks. dist., with a notch at base.

A fir, 37 ins. diam., bears N.81°W., 26 lks.
dist., with a notch at base.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.

N 1/16	
S 13	S 18
1985	

from which new bearing trees

A fir, 16 ins. diam., bears N. 26 $\frac{3}{4}$ °E., 63 lks.
dist., mkd. N 1/16 S18 BT.