

# County Surveyor's Record, Douglas County, Oregon

18746

Dependent Resurvey of a Portion of the East Boundary,  
T. 30 S., R. 10 W., Willamette Meridian, Oregon


18746

CHAINS

A fir, 26 ins. diam., bears N.56<sup>1</sup>/<sub>2</sub>°W., 111 lks.  
dist., mkd. N 1/16 S13 BT.

The corner is located in edge of timber, bears E. and W.

From this point, an electronic control point at latitude 42° 58' 59.31" N., longitude 123° 48' 42.89" W., as determined by the doppler method of global positioning using Magnavox MX-1502 receivers, in 1985, established in conjunction with this survey, bears N.17° 23' 10"E., 108.627 chs. dist., monumented with an iron rod, 36 ins. long, 5/8 in. diam., firmly set flush in a concrete pad, 1 ft. in diam., with a seated aluminum cap mkd.



N. 0° 10' W., beginning new measurement.

Descend over N. slope, through heavy timber and dense undergrowth.

4.80 Middle Fork of the Coquille River, 70 lks. wide, course S.75°W.; asc. over S. slope, changing to SW. slope.

6.00 State Highway No. 42, asphalt surface, 45 lks. wide, bears N. 80° E., and S. 80° W.

20.11 The cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., perpetuated and recorded by John N. Gearhart, Coos County Surveyor, in 1951, and further perpetuated and recorded by Vernon R. Tracy, Douglas County Deputy Surveyor, in 1964, monumented with an iron post, 1<sup>1</sup>/<sub>4</sub> ins. diam., loosely set in a mound of stone, 1 ft. base, with brass cap mkd. DOUGLAS COUNTY SURVEYORS OFFICE T30S R9W R10W S7 S12 S13 S18 1964, from which the remains of the original bearing trees:

A sawed cedar stump, 35 ins. diam., bears N.46°E., 35 lks. dist., with scribe marks S7 183 BT visible on open blaze. (Record, 41<sup>1</sup>/<sub>2</sub> lks.)

A decayed cedar stump, 30 ins. diam., bears S.63<sup>1</sup>/<sub>2</sub>°W., 42<sup>1</sup>/<sub>2</sub> lks. dist., no marks visible.

A sawed cedar stump, 42 ins. diam., bears N.64°W., 50 lks. dist., with healed blaze. (Record, N.56<sup>1</sup>/<sub>2</sub>°W., 37 lks.)

and the remains of a bearing tree mkd. by Gearhart

A sawed cedar stump, 25 ins. diam., bears West, 30 lks. dist., with scribe marks S12 183 BT visible on open blaze.

and bearing trees mkd. by Tracy

A myrtle, 10 ins. diam., bears N.65°E., 10<sup>1</sup>/<sub>2</sub> lks. dist., with illegible scribe marks visible on partially healed blaze.

An alder, 20 ins. diam., bears S.4°E., 58 lks. dist., with healed blaze.

An alder, 20 ins. diam., bears N.33°W., 55 lks. dist., with healed blaze.

At the corner point