

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the East Boundary,
T. 30 S., R. 10 W., Willamette Meridian, Oregon

18747

CHAINS

Set a brass tablet, 3¼ ins. diam., 3½ in. stem, in an iron pipe, 1 in. diam., 12 ins. long, in a drill hole, 8 ins. deep, in solid bedrock, with top mkd.

T 30 S			
R 10 W	R 9 W		
S 12	S 7		
S 13	S 18		
1985			

from which new bearing trees

A fir, 17 ins. diam., bears N. 8° E., 72 lks. dist.,
mkd. T30S R9W S7 BT.

A fir, 17 ins. diam., bears S. 71° W., 45 lks.
dist., mkd. T30S R10W S13 BT.

A fir, 10 ins. diam., bears N. 75° W., 47½ lks. dist.,
mkd. T30S R10W S12 BT.

Deposit iron post at base of iron pipe.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, alder, maple, myrtle, and madrone; undergrowth, salmonberry, huckleberry, salal, Oregon grape, poison oak, ferns, and grass.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 30 S., R. 10 W., Willamette Meridian, Oregon

(Restoring the survey by William M. Bushey, in 1893, the resurvey by James E. Jelley, in 1971, the resurvey by Jack W. Bowder, in 1976, and the remonumentation by Harvey E. Wofford, John P. Farnsworth, and Joel E. Robb, in 1978-83)

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., perpetuated and recorded by John M. Powell, Douglas County Deputy Surveyor, in 1965, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S			
R			R
10	S 13	S 18	9
W	S 24	S 19	W
1965			

from which the remains of the original bearing tree

A sawed fir stump, 68 ins. diam., bears S. 85½° W.,
211 lks. dist., with illegible scribe marks
visible on opened blaze.

and bearing trees mkd. by Powell

A fir, 22 ins. diam., bears N. 47° E., 21 lks.
dist., with healed blaze.

A hemlock, 10 ins. diam., bears S. 7° E., 19½ lks.
dist., with healed blaze.

A cedar, 23 ins. diam., bears S. 54° W., 10½ lks.
dist., with healed blaze.