

# County Surveyor's Record, Douglas County, Oregon

T. 19 S., R.9 W., Willamette Meridian, Oregon

18751

CHAINS

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the corner of sections 25 and 36 only, on the east boundary of township 19 south, range 10 west, as determined from a tie to GPS Station No. 191036, located in southwest ¼, section 36, township 19 south, range 10 west, established by David Evans and Associates, Inc., Portland, Oregon for the United States Forest Service in 1988, is as follows:

Latitude 43° 52' 43.15" N. Longitude 123° 49' 52.83" W.

The geographic position (NAD 1927) of the corner of sections 12 and 13 only, on the east boundary of township 19 south, range 10 west, as determined from a tie to GPS Station No. 191013, located in northwest ¼, section 13, township 19 south, range 10 west, established by David Evans and Associates, Inc., Portland, Oregon, for the United States Forest Service in 1988, is as follows:

Latitude 43° 55' 54.11" N. Longitude 123° 49' 34.12" W.

The mean magnetic declination is 18½° East.

Corrective Dependent Resurvey of a Portion of the East Boundary,  
T. 19 S., R. 10 W., Willamette Meridian, Oregon

(Restoring the survey by Henry L. Chandler, in 1899, Correcting the resurvey by Thomas A Tillman, Robert L. Holm, and Floyd A. Brooks, in 1957-58, and correcting the retracement by Donald R. Beck and Peter A. Peterson, in 1968,76)

Beginning at the cor. of secs. 25 and 36 only, perpetuated by Milo E. Godfrey, Registered Land Surveyor No. 496, in 1964, and recorded in Douglas County Corner Renewal No. 2, also perpetuated by Ernesto R. Alvarado for the Douglas County Surveyor's Office in 1982, and recorded in Douglas County Corner Renewal No. 29, and remonumented by Alvarado in 1984, and recorded in Douglas County Corner Renewal No. 37; monumented with an iron post, 1½ ins. diam., firmly set in the center of a root hole and in a collar of stone, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T19S			
R	S	25	R
10	—	—	9
W	S	36	W
1964			

from which the original bearing trees

A root hole, bears S.83° W., 71 lks. dist., lying alongside is an uprooted hemlock, 38 ins. diam., with old chop marks and illegible scribe marks visible on partially healed blaze. (Record, fir.)

A root hole, bears N.3½° W., 6 lks. dist., lying alongside is an uprooted fir stump, 40 ins. diam., with healed blaze.

and the bearing trees mkd. by Alvarado

An iron rod, 3/8 in. diam., firmly set, projecting 6 ins. from a hemlock stump, 43 ins. diam., 6 ft. high, bears N. 74° 55' E., 116.4 lks. dist., with scribe marks CSBT visible on unhealed blaze and a spike.