

County Surveyor's Record, Douglas County, Oregon

18752

Corrective Dependent Resurvey of a Portion of the East Boundary,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

An iron rod, 3/8 in. diam., firmly set, projecting 6 ins. from a hemlock stump, 36 ins. diam., 6 ft. high, bears S. 40° 15' W., 76.0 lks. dist., with scribe marks T19S R10W S36 CS BT visible on unhealed blaze and a spike.

An iron rod, 3/8 in. diam., firmly set, projecting 12 ins. from a hemlock stump, 38 ins. diam., bears S. 70° 45' W., 77.0 lks. dist., with scribe marks CSBT visible on unhealed blaze and a spike.

Lying down the hill is the original corner tree, an uprooted fir stump, 28 ins. diam., with two healed blazes.

From this point, the United States Forest Service GPS Station No. 191036, bears S. 41° 30' 20" W., 71.294 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set in concrete, flush with ground surface, with aluminum cap mkd. GPS 191036 + 1988.


N. 4° 16' 00" E., on the E. bdy. of sec. 25.

Descend NE. slope, through logged area.

9.100 From this point, the original closing cor. of secs. 30 and 31, T. 19 S., R. 9 W., monumented with the remains of the original corner tree, a fir snag stump, 30 ins. diam., with flattened pitch seams visible in top, in 20 inch core diam., facing N., E., and S., bears West, 0.725 chs. dist. Lying alongside is the log, sawed off end and uncovered scribe marks 9W on what was the E. side.

At the corner point

Drive an iron rod, 24 ins. long, 5/8 diam., 20 ins. into the top center of the corner stump, with aluminum cap mkd.



from which

A cedar, 35 ins. diam., bears N. 47½ E., 160 lks. dist.,
mkd. T19S R9W S30 CC BT.

Over level ground.

10.725 From this point, the closing cor. of secs. 30 and 31, T. 19 S., R. 9 W., erroneously reestablished by Tillman, Holm, and Brooks in 1957-58, bears East, 0.060 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record. Remove the iron post and obliterate the scribe marks on the bearing trees.

11.70 Begin descending N. slope, over river bank.

13.00 North Fork Smith River, 80 lks. wide, course S. 70° E.; asc. gradual SW. slope, through timber.

24.00 Spur, slopes S. 40° W.; desc. gradual NW. slope.

31.00 Bottom of descent; over level ground.

43.00 North Fork Smith River, 80 lks. wide, course W.; asc. SE. slope.

46.425 The ¼ sec. cor. of sec. 25 only, determined from the bearing trees; the corner point falls in a small slide, the monument has been disturbed and was found down the hill, from which the bearing trees