

# County Surveyor's Record, Douglas County, Oregon

18754 Corrective Dependent Resurvey of a Portion of the East Boundary,  
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">An alder snag, 12 ins. diam., 2 ft. high, bears N.9° W., 29 lks. dist., no marks. (Record, 31 lks.)</p> <p>and the bearing tree mkd. by Tillman, Holm and Brooks</p> <p style="text-align: center;">A fir, 26 ins. diam., bears N. 26° W., 46 lks. dist., with healed blaze.</p> <p>From this point, the United States Forest Service GPS Station No. 191013, bears S. 73° 21' 50" W., 60.370 chs. dist., monumented with an aluminum post, 2½ ins. diam., firmly set flush with ground surface, with aluminum cap mkd. GPS 191013 + 1988.</p> <p>N. 1° 15' 00" E., on the E. bdy. of sec. 12.</p> <p>Descend NE. changing to N. slope, timber to E., logged area to W., posting true line.</p>
4.40	Ravine, drains N. 60° E.; asc. SE. slope.
8.50	Spur, slopes S. 70° E.; desc. NE. slope, through timber.
8.945	True point for the closing cor. of secs. 7 and 18, T. 19 S., R. 9 W., hereinafter described.
	Enter logged area.
11.00	Ravine, drains S. 40° E.; asc. S. slope.
16.70	Spur, slopes S. 70° E.; desc. broken NE. slope.
21.20	Ravine, drains S. 80° E.; asc. S. slope.
25.80	Spur, slopes N. 80° E.; desc. rolling NE. slope.
26.40	Gravel road, 20 lks. wide, bears E. and W.
38.390	<p>The ¼ sec. cor. of sec. 12 only, monumented with the original sandstone, 12 x 8 x 7 ins., lying on its side, flush with ground surface, mkd. ¼ on W. side, from which the remains of an original bearing tree:</p> <p style="text-align: center;">A hemlock stump, 22 ins. diam., bears S. 58° W., 14 lks. dist., with healed blaze on NE. face; sawed open and found scribe marks ¼ on 6 in. core diam.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:</p> <div style="text-align: center; margin: 10px 0;"> <p>T19S</p> <p>R10W      R9W</p> <p style="margin-left: 100px;"> </p> <p>¼ S 12</p> <p style="margin-left: 100px;">1989</p> </div> <p>from which the bearing trees mkd. by Tillman, Holm and Brooks</p> <p style="text-align: center;">A fir, 21 ins. diam., bears N. 73½° W., 39 lks. dist., with healed blaze.</p> <p style="text-align: center;">A fir, 30 ins. diam., bears N. 28½° W., 66 lks. dist., with healed blaze.</p> <p>Deposit corner stone alongside and white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the ¼ sec. cor. of sec. 12 only, erroneously reestablished by Tillman, Holm, and Brooks in 1957-58, bears</p>