

County Surveyor's Record, Douglas County, Oregon

18758 Corrective Dependent Resurvey of a Portion of the East Boundary,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set an iron rod, 24 ins. long, 5/8 in. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">BLM AM 1989</p>
31.60	Dry creek bed, 2 lks. wide, course S. 30° E.; asc. S. slope.
35.50	Spur, slopes S. 30° E.; asc. E. slope.
38.50	U.S. Forest Servie Road No. 4890-939, gravel, 20 lks. wide, bears N. 50° E. and S. 40° W., in a curve.
39.000	<p>The ¼ sec. cor. of sec. 1 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T19S ¼ S 1 R10W 1957</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears S. 60½° W., 112 lks. dist., with healed blaze. (Record, 113 lks.)</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N. 42½° W., 60 lks. dist., with healed blaze. (Record, 62 lks.)</p> <p>Corner is located on a spur, slopes N. 60° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 50' 00" E., beginning new measurement.</p> <p>Descend NW. slope. through timber.</p>
3.10	Spur, slopes N. 20° W.; desc. NE. changing to NW. slope.
8.770	<p>The ¼ sec. cor. of sec. 6 only, T. 19 S., R. 9 W., monumented with an iron post, firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">¼ S 6 T19S R9W 1958</p> <p>from which the remains of bearing trees mkd. by Tillman, Holm and Brooks</p> <p style="padding-left: 40px;">A root hole, bears N. 77½° E., 116 lks. dist., lying alongside is a maple, 20 ins. diam., no marks visible.</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears S. 52½° E., 117 lks. dist., with fragmentary scribe marks visible in partially healed blaze. (Record, S. 53½° E.)</p> <p>and a bearing tree mkd. by Ronald E. Stuntzner, Registered Land Surveyor No. 1342, and Clyde F. Mulkins, Registered Land Surveyor No. 2006, in 1983, and recorded in Lane County Survey No. 26,183.</p> <p style="padding-left: 40px;">A cedar, 43 ins. diam., bears S. 81° E., 122 lks. dist., with scribe marks ¼ S6 BT visible on partially healed blaze.</p> <p>and a new accessory</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 87° 58' E., 94.1 lks. dist., with brass cap mkd. RM ¼ S6 62.1 FT TO COR 1989 and an arrow pointing to the corner.</p>