

County Surveyor's Record, Douglas County, Oregon


Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 9 W., Willamette Meridian, Oregon

18759

CHAINS

(Restoring the survey executed by Henry L. Chandler,
in 1899, and the resurvey by Thomas A. Tillman,
Robert L. Holm, and Floyd A. Brooks, in 1957-58)

From the cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.



from which the remains of the original bearing trees

A root hole, bears N.22°E., 4 lks. dist.

A hemlock, 35 ins. diam., bears S. 40° W., 35 lks. dist., with healed blaze.

A fir snag, size indeterminate, bears N. 75° W., 13 lks. dist., no marks visible.

and the bearing trees mkd. by Tillman, Holm and Brooks

A hemlock, 8 ins. diam., bears N. 79° E., 41 lks. dist., with healed blaze. (Record, N. 83½° E.)


A fir, 32 ins. diam., bears S. 54½° E., 67 lks. dist., with healed blaze.

A fir, 37 ins. diam., bears N. 13° W., 27 lks. dist., with healed blaze. (Record, 29 lks.)

N. 88° 48' 00" W., bet. secs. 7 and 18.

Descend NW. slope, through timber.

- 1.35 Creek, 3 lks. wide, course N. 30° E.; asc. NE. slope.
- 3.70 Top of ascent, slopes N.; desc. N. slope.
- 10.10 Ravine, drains N. 20° E.; asc. NE. slope.
- 12.80 Top of ascent, slopes N.; desc. N. changing to NW. slope.
- 26.80 Spur, slopes N. 40° W.; desc. SW. slope.
- 33.50 Kentucky Falls Trail, 5 lks. wide, bears N. 50° W. and S. 50° E.
- 38.90 Same trail, bears N. 40° W. and S. 40° E.
- 39.485 The ¼ sec. cor. of secs. 7 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.



FDOK
D. Baker
3/97
M124-48

from which the remains of bearing trees mkd. by Tillman, Holm and Brooks

A fir, 23 ins. diam., bears S. 38° E., 62 lks. dist., with healed blaze. (Record, S. 32° E., 63 lks.)

A root hole, bears N. 42° W., 66 lks. dist., lying alongside is a fir, 27 ins. diam., with healed blaze.