

County Surveyor's Record, Douglas County, Oregon

18760

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R.9 W., Willamette Meridian, Oregon

CHAINS	
	and a new bearing tree
	A fir, 27 ins. diam., bears N. $32\frac{1}{2}^{\circ}$ W., 98 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

	N. $88^{\circ} 50' 00''$ W., beginning new measurement.
	Descend SW. slope, through timber.
0.40	Toe of hill, bears N. 30° W. and S. 30° E.; over level flood plain.
0.90	Abandoned creek channel, 20 lks. wide, course S.
2.60	North Fork Smith River, 50 lks. wide, course S.; asc. NE. slope.
10.10	Overgrown rock road, 20 lks. wide, bears N. 20° W. and S. 20° E.; asc. broken NE. slope.
19.715	Point for the W 1/16 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd:
	$\begin{array}{c} \underline{S 7} \\ W 1/16 S 18 \\ 1989 \end{array}$
	from which
	A stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 28 ins. in the ground, for a reference monument, bears S. $89^{\circ} 18'$ W., 72.6 lks. dist., with brass cap mkd. RM W 1/16 S18 47.9 FT TO COR 1989 and an arrow pointing to the corner.
	and the bearing trees mkd. by Daniel W. Baker, Registered Land Surveyor No. 1978, in 1988, and recorded in Douglas County Surveyor Map 107-1
	A hemlock, 10 ins. diam., bears S. $51\frac{1}{2}^{\circ}$ E., 32 lks. dist., with scribe marks W 1/16 S18 BT visible on partially healed double blaze.
	A fir, 16 ins. diam., bears N. 61° W., $49\frac{1}{2}$ lks. dist., with scribe marks W 1/16 S7 BT visible on partially healed double blaze.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	From this point, a point established as the W 1/16 sec. cor. of secs. 7 and 18 by W.E. Hardy, U.S. Forest Service Forestry Technician, in 1964, record held at Mapleton Ranger Station, bears N. $42\frac{1}{2}^{\circ}$ W., 0.050 chs. dist. This point was not established by a registered land surveyor/engineer, was established using improper control and is not utilized in this survey, determined from the bearing trees mkd. by Hardy:
	An alder, 16 ins. diam., bears N. $10\frac{1}{2}^{\circ}$ E., 12 lks. dist., no marks visible.
	An alder, 12 ins. diam., bears S. $15\frac{1}{4}^{\circ}$ W., 27 lks. dist., with an aluminum tag.
	From this same point, a point established as the W 1/16 sec. cor. of secs. 7 and 18 by Daniel W. Baker, Registered Land Surveyor No. 1978, in 1988, and recorded in Douglas County Survey Map 107-1, bears N. 31° W., 0.017 chs. dist., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 3 ins. above ground, with aluminum cap mkd. T19S R9W W1/16 S7 S18 RLS 1978 1988. This point