

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 9 W., Willamette Meridian, Oregon

18761

CHAINS

was established using improper control and is not utilized in this survey.

Ascend NE. slope, logged area to N. and timber to S., posting true line.

21.70 Spur, slopes S. 50° E.; desc. SW. slope.

26.30 Bottom of descent, slopes S.; asc. SE. slope.

27.40 Spur, slopes S.; desc. SW. slope.

28.60 Ravine, drains S. 20° E.; asc. SE. slope.

30.20 Top of ascent, slopes S.; desc. S. changing to SW. slope.

36.60 Ravine, drains S. 50° E.; asc. NE. slope.

39.430 The original closing cor. of secs. 7 and 18, monumented with a sandstone, 18 x 18 x 6 ins., in two pieces, loosely set 2 ins. in the ground, mkd. CC on the E. face, with 4 grooves on the S. and 2 grooves on the N. faces, from which the original bearing trees:

A fir stump, 30 ins. diam., bears N. 19° E., 36 lks. dist., with healed blaze. (Record, N. 17¼° E., 34 lks.)

A fir, 40 ins. diam., bears S. 19¼° E., 45 lks. dist., with healed blaze. (Record, S. 16° E., 48 lks.)


Reset stone in place, flush with the ground surface.

39.440 Intersect the E. bdy. of sec. 12, T. 19 S., R. 10 W.

True point for the closing cor. of secs. 7 and 18.

From this point, the closing cor. of secs. 7 and 18 established by Tillman, Holm, and Brooks in 1957-58, bears N. 88° 50' 00" W., 0.040 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1989 1958, reset the monument flush with the ground surface, obliterated the scribe marks on the NE. bearing tree and at the true corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:



from which

A stainless steel post, 28 ins. long, 2½ ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 87° 19' E., 82.3 lks. dist., with brass cap mkd. RM T19S R9W S18 54.3 FT TO COR 1989 and an arrow pointing to the corner.

and a bearing tree mkd. by Tillman, Holm and Brooks

A hemlock, 15 ins. diam., bears S. 62¼° E., 54 lks. dist., with healed blaze.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this same point, the cor. of secs. 12 and 13 only, T. 19 S., R. 10 W., bears S. 1° 15' 00" W., 8.945 chs. dist., hereinbefore described.