

County Surveyor's Record, Douglas County, Oregon

18762

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented with an iron post, 2$\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S\ 6}{S\ 7}$ ✓ T19S R9W 1958 </p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir snag, 12 ins. diam., 10 ft. high, bears N. 24° E., 15 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 10 ins. diam., 1 ft. high, bears S. 67° E., 15 lks. dist., no marks. (Record, S. 73$\frac{1}{2}$° E.)</p> <p>and the remains of bearing trees mkd. by Tillman, Holm and Brooks</p> <p style="padding-left: 40px;">A fir snag, 28 ins. diam., 20 ft. high, bears N. 22° E., 38 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 26 ins. diam., bears S. 29° E., 86 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>and a new accessory</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 87° 26' W., 85.4 lks. dist., with brass cap mkd. RM $\frac{1}{4}$ S7 56.3 FT TO COR 1989 and an arrow pointing to the corner.</p> <p>N. 89° 09' 30" W., bet. secs. 6 and 7.</p> <p>Ascend SE. slope, through timber, posting true line.</p>
7.90	Spur, slopes S. 45° E.; desc. SW. slope.
12.50	Enter logged area to N., edge bears N. and W.
15.60	Creek, 2 lks. wide, course S. 30° E.; asc. NE. changing to N. slope.
25.60	Small spur, slopes N.; desc. NW. slope.
26.50	Ravine, drains N.; asc. NE. slope.
37.30	Spur, slopes S. 60° E.; asc. S. slope.
38.20	Gravel road, 20 lks. wide, bears N. 50° E. and S. 70° W., in a curve.
39.310	<p>The original closing cor. of secs. 6 and 7, monumented with a sandstone, 16 x 12 x 6 ins., crumbling into pieces, firmly set flush with ground surface, mkd. CC on E. face and other indistinct marks, from which the remaining original bearing trees:</p> <p style="padding-left: 40px;">A fir snag stump, 40 ins. diam., bears N. 56$\frac{1}{2}$° E., 253 lks. dist., no marks visible. (Record, N. 56° E., 260 lks.)</p>
39.325	<p>Intersect the E. bdy. of sec. 1, T. 19 S., R. 10 W.</p> <p>True point for the closing cor. of secs. 6 and 7.</p> <p>From this point, the closing cor. of secs. 6 and 7 established by Tillman, Holm and Brooks in 1957-58, bears N. 89° 09' 30" W., 0.045 chs. dist., monumented with an iron post, 2$\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. and witnessed as described in the official record, except no evidence of the SE. bearing tree remains. Amended the marks on the brass cap to read AM</p>