

County Surveyor's Record, Douglas County, Oregon

18770

Dependent Resurvey of a Portion of the East Boundary,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS																
	N. 3° 44' 00" E., beginning new measurement.															
	Descend broken NE. slope, through logged area.															
12.335	Point for the S 1/16 sec. cor. of sec. 13 only.															
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:															
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="padding-right: 10px;">S 1/16</td><td> </td><td></td></tr> <tr><td style="padding-right: 10px;">S 13</td><td> </td><td></td></tr> <tr><td></td><td> </td><td style="text-align: center;">1989</td></tr> </table>	S 1/16			S 13					1989						
S 1/16																
S 13																
		1989														
	from which															
	A fir, 5 ins. diam., bears S. 31½° W., 67½ lks. dist., mkd. S 1/16 S13 BT.															
	A fir, 3 ins. diam., bears N. 28¾° W., 27 lks. dist., mkd. X BT.															
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.															
	Ascend SE. slope, through logged area.															
13.30	Spur, slopes E.; desc. broken NE. slope.															
35.625	The ¼ sec. cor. of sec. 13 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.															
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="padding-right: 10px;">¼</td><td> </td><td></td></tr> <tr><td style="padding-right: 10px;">T19S</td><td> </td><td></td></tr> <tr><td style="padding-right: 10px;">R10W</td><td> </td><td></td></tr> <tr><td style="padding-right: 10px;">S 13</td><td> </td><td></td></tr> <tr><td></td><td> </td><td style="text-align: center;">1958</td></tr> </table>	¼			T19S			R10W			S 13					1958
¼																
T19S																
R10W																
S 13																
		1958														
	from which the remains of bearing trees mkd. by Tillman, Holm and Brooks															
	A fir stump, 50 ins. diam., bears S. 79½° W., 40 lks. dist., with healed blaze. (Record, S. 70° W.)															
	A cedar snag, 34 ins. diam., 1 ft. high, bears N. 80¼° W., 67 lks. dist., no marks visible.															
	and new bearing trees															
	A fir, 7 ins. diam., bears N. 82¼° W., 97½ lks. dist., mkd. X BT.															
	A fir, 14 ins. diam., bears N. 41° W., 126½ lks. dist., mkd. ¼ S13 BT.															

	N. 4° 09' 00" E., beginning new measurement.															
	Ascend S. slope, through logged area, posting true line.															
4.10	Spur, slopes S. 30° E.; asc. E. slope.															
9.795	The ¼ sec. cor. of sec. 18 only, T. 19 S., R. 9 W., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd.															
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="padding-right: 10px;">¼</td><td> </td><td></td></tr> <tr><td style="padding-right: 10px;">T19S</td><td> </td><td></td></tr> <tr><td style="padding-right: 10px;">R9W</td><td> </td><td style="padding-left: 10px;">V</td></tr> <tr><td style="padding-right: 10px;">S 18</td><td> </td><td></td></tr> <tr><td></td><td> </td><td style="text-align: center;">1958</td></tr> </table>	¼			T19S			R9W		V	S 18					1958
¼																
T19S																
R9W		V														
S 18																
		1958														