

# County Surveyor's Record, Douglas County, Oregon

18772

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 S., R. 10 W., Willamette Meridian, Oregon

**CHAINS**

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:

T19S    R10W  
           ¼ S 24  
           ¼ S 25  
           1989

from which

A fir, 43 ins. diam., bears S. 58° W., 37 lks. dist.,  
mkd. ¼ S25 BT.

A cedar, 25 ins. diam., bears N. 2° W., 38 lks. dist.,  
mkd. ¼ S24 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Corner is located on a spur, slopes N. 70° E.

Ascend NE. changing to broken N. slope, through timber.

62.60 U.S. Forest Service Road No. 48-922, gravel, 20 lks. wide, bears N. 50° W. and S. 50° E.; asc. NE. slope, through logged area.

64.90 U.S. Forest Service Road No. 48-932, gravel, 25 lks. wide, bears N. 20° W. and S. 30° W., in curve and on ridge, bears N. 30° W. and S. 30° E.; desc. W. slope, through timber.

69.80 Ravine, drains S. 50° W.; asc. rolling SE. changing to S. slope.

76.290 Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:

T19S    R10W  
       S 23 | S 24  
       S 26 | S 25  
           1989

from which

A fir, 93 ins. diam., bears N.55° E., 34 lks. dist.,  
mkd. T19S R10W S24 BT.

A hemlock, 17 ins. diam., bears S. 75° E., 26 lks. dist.,  
mkd. T19S R10W 25 BT.

A cedar, 10 ins. diam., bears S. 53° W., 30½ lks. dist.,  
mkd. T19S R10W S26 BT.

A fir, 21 ins. diam., bears N. 71¼° W., 44 lks. dist.,  
mkd. T19S R10W S23 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the cor. of secs. 22, 23, 26, and 27, bears N. 87° 23' 00" W., 76.320 chs. dist., hereinafter described.

From this same point, the cor. of secs. 25, 26, 35 and 36 re-established by James W. Prochnau, Registered Professional Engineer No. 4185, in 1971, and recorded in Douglas County Survey May 43-22, bears S. 1° 23' 00" E., 91.970 chs. dist. This position was set with reference to original line blazes and calls of topography, is harmoniously related to existing evidence of the original survey and is accepted as a careful and faithful determination of the original corner position. Monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.