

18774

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

From this point, the United States Forest Service GPS Station No. 191024, bears S. 20° 53' 50" E., 25.342 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set in concrete, flush with ground surface, with aluminum cap mkd. GPS 191024 + 1988.

Ascend S. slope.

48.40 Spur, slopes S. 60° E.; desc. broken NE. slope.

60.00 Spur, slopes S.; asc. E. changing to SE. slope.

67.80 Spur, slopes S. 60° E.; desc. NE. slope.

69.105 Point for the N 1/16 sec. cor. of secs. 23 and 24.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:

N 1/16	
S 23	S 24
1989	

from which

A fir, 76 ins. diam., bears S. 68½° E., 65 lks. dist.,
mkd. N. 1/16 S24 BT.

A hemlock, 27 ins. diam., bears S. 10¼° W., 39 lks. dist.,
mkd. N 1/16 S23 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Descend broken NE. slope.

81.00 Enter logged area, edge bears NE. and SW.; asc. SW. changing to rolling S. slope.

84.10 U.S. Forest Service Road No. 48-910, 25 lks. wide, bears N. 70° W. and S. 70° E.

92.140 Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:

T19S	R10W
S 14	S 13
S 23	S 24
1989	

from which

A fir, 10 ins. diam., bears N. 25° E., 14 lks. dist.,
mkd. T19S R10W S13 BT.

A fir, 8 ins. diam., bears S. 36½° E., 11½ lks. dist.,
mkd. T19S R10W S24 BT.

A fir, 10 ins. diam., bears S. 24° W., 25½ lks. dist.,
mkd. T19S R10W S23 BT.

A fir, 10 ins. diam., bears N. 76½° W., 43 lks. dist.,
mkd. T19S R10W S14 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., bears N. 88° 27' 30" W., 392.395 chs. dist., monumented with a badly rusted iron post, 2 ins. diam., and filled with concrete, firmly set, projecting 2 ins. above ground, with top 12"