

County Surveyor's Record, Douglas County, Oregon

18776

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS							
	<p style="text-align: center;">A fir, 6 ins. diam., bears S. 23° E., 17 lks. dist., mkd. E 1/16 S24 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend NE. slope.</p>						
31.40	Spur, slopes S. 60° E.; asc. S. slope.						
33.90	Overgrown rock road, 20 lks. wide, bears N. 70° E. and S. 70° W.						
35.20	Top of ascent, slopes S.; desc. S. slope.						
38.670	<p>Point for the ¼ sec. cor. of sec. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:</p> <div style="text-align: center;"> <p>T19S R10W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">¼</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">S 13</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 24</td> </tr> <tr> <td></td> <td>1989</td> </tr> </table> </div> <p>from which</p> <p style="text-align: center;">A fir, 13 ins. diam., bears S. 31¼° W., 53½ lks. dist. mkd. ¼ S24 BT.</p> <p style="text-align: center;">A fir, 9 ins. diam., bears N. 12° W., 20½ lks. dist., mkd. ¼ S13 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as an approximate ¼ sec. cor. of secs. 13 and 24 by C.E. Worthylake et al., employees of Davidson Industries, Inc., in 1968, record held at Davidson Industries, Inc., Mapleton, Oregon, bears S. 77° 52' W., 1.312 chs. dist., determined from the bearing trees mkd. by Worthylake et al.:</p> <p style="text-align: center;">A cedar stump, 48 ins. diam., bears N. 77° E., 58 lks. dist., no scribe marks on unhealed blaze.</p> <p style="text-align: center;">A fir, 18 ins. diam., at base of old growth fir, 6 ft. diam., bears N. 65° W., 80 lks. dist., with healed blaze.</p> <p>Over S. slope, posting true line.</p>	¼	S 13		S 24		1989
¼	S 13						
	S 24						
	1989						
38.90	Ravine, drains S. 30° E.; asc. SE. slope.						
39.90	Enter timber, edge bears N. and S. near SE. cor. of timber; thence along and near S. edge of timber.						
42.40	Spur, slopes S. 40° E.; desc. SW. slope.						
44.30	Ravine, drains S.; asc. SE. slope.						
47.90	Spur, slopes S. 30° E.; desc. SW. changing to rolling S. slope.						
55.50	Creek, 2 lks. wide, course S. 20° E.; asc. SE. changing to E. slope.						
58.005	<p>Point for the W 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">W 1/16</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">S 13</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 24</td> </tr> <tr> <td></td> <td>1989</td> </tr> </table> </div>	W 1/16	S 13		S 24		1989
W 1/16	S 13						
	S 24						
	1989						