

County Surveyor's Record, Douglas County, Oregon

13

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

18777

CHAINS

from which

A stainless steel post, 28 ins. long, 2½ ins. diam., set 28 ins. in the ground, for a reference monument, bears N. 85° 56' E., 67.7 lks. dist., with brass cap mkd. RM W 1/16 S13 44.7 FT TO COR 1989 and an arrow pointing to the corner.

A fir, 8 ins. diam., bears S. 11½° E., 70 lks. dist., mkd. W 1/16 S24 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point established as an approximate W 1/16 sec. cor. of secs. 13 and 24 by C.E. Worthylake et al., employees of Davidson Industries, Inc., in 1968, record held by Davidson Industries, Inc., Mapleton, Oregon, and perpetuated as a working corner by a U.S. Forest Service cutting boundary agreement survey in 1974, record held at Mapleton Ranger Station, bears S. 46° 33' W., 0.628 chs. dist., monumented with a mound of stone, 2 ft. base, 1 ft. high, on a sandstone outcrop, 4 ft. high, 10 ft. wide, downhill is a ¼ in. angle iron lying loose on the ground, from which the bearing tree mkd. by Worthylake et al.:

A cedar, 30 ins. diam., bears N. 6½° W., 49 lks. dist., with partially healed blaze.

and the bearing tree mkd. by the U.S. Forest Service

A maple, 30 ins. diam., bears S. 64¼° W., 45 lks. dist., with an aluminum tag.

Ascend E. changing to broken S. slope.

58.50 Enter timber, near NW. cor. of logged area.

72.40 Enter logged area, edge bears N. 10° W. and S. 10° E.; asc. S. slope.

77.340 The cor. of secs. 13, 14, 23 and 24.

N. 3° 22' 30" E., bet. secs. 13 and 14.

Ascend S. slope, through logged area.

4.70 U.S. Forest Service Road No. 48-911, gravel, 20 lks. wide, bears N. 70° E. and S. 70° W.

6.50 Divide between the Siuslaw and Smith River drainages, bears N. 80° E. and S. 80° W.; desc. broken N. slope.

7.60 U.S. Forest Service Road No. 4890, gravel, 25 lks. wide, bears N. 80° E. and S. 80° W.

46.055 Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:

| | |
|------|------|
| T19S | R10W |
| S 14 | S 13 |
| 1989 | |

from which