

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

18779

CHAINS

A fir, 11 ins. diam., bears S. 70 $\frac{1}{4}$ ° W., 25 lks. dist.,
mkd. T19S R10W S14 BT.

A fir, 10 ins. diam., bears N. 30° W., 20 lks. dist.,
mkd. T19S R10W S11 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Corner is located on a SE. slope near the head of a ravine, drains NE.

From the cor. of secs. 12 and 13, on the E. bdy. of the Tp.

S. 89° 09' 30" W., bet. secs. 12 and 13.

Ascend NE. slope, through timber, posting true line.

- 1.20 Spur, slopes N.; desc. NW. slope.
- 2.30 Ravine, drains N. 10° W.; asc. NE. changing to N. slope.
- 4.30 Spur, slopes N. 30° W.; desc. rolling NW. slope.
- 6.90 Ravine, drains N. 40° E.; asc. NE. slope, through logged area.
- 15.00 U.S. Forest Service Road No. 4890, gravel, 20 lks. wide, bears N. 20° W. and S 20° E.
- 15.30 Gravel road, 15 lks. wide, bears N. 30° W. and S. 30° E.
- 16.30 Divide between Siuslaw and Smith River drainages, bears N. 10° W. and S. 10° E.; desc. W. slope.
- 19.655 The E 1/16 sec. cor. of secs. 12 and 13, established by Daniel W. Baker, Registered Land Surveyor No. 1978, in 1989, recorded in Douglas County Survey Map 110-15, and is accepted as the corner; monumented with an aluminum tablet, 3 $\frac{1}{2}$ ins. diam., set flush in sandstone bedrock, mkd.

T19S R10W
E 1/16 $\frac{S\ 12}{S\ 13}$
PLS 1978
1988

from which the bearing trees mkd. by Baker in 1988, recorded in Douglas County Map 107-1 and reused in Douglas County Survey Map 110-15

A hemlock, 13 ins. diam., bears S. 26° E., 77 lks. dist.,
with scribe marks E 1/16 S13 BT visible on unhealed double blaze.

A fir, 25 ins. diam., bears N. 72 $\frac{1}{2}$ ° W., 66 lks. dist.,
with healed blaze and scribe marks E 1/16 S12 BT visible on unhealed double blaze. This is also the NW. bearing tree mkd. by Alan D. Reid, U.S. Forest Service Forester, in 1958, and recorded in Lane County Reestablishment No. 2187.

and the bearing object and bearing tree set and mkd. by Alan D. Reid, U.S. Forest Service Forester, in 1958, and recorded in Lane County Reestablishment No. 2187

An iron pipe, 1 in. diam., firmly set, projecting 6 ins.
above ground, bears N. 8° 46' E., 55.9 lks. dist.

A fir, 40 ins. diam., bears N. 29 $\frac{1}{2}$ ° W., 104 lks. dist., with healed blaze.