

# County Surveyor's Record, Douglas County, Oregon

18780

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 S., R. 10 W., Willamette Meridian, Oregon

**CHAINS**

and a new accessory

A stainless steel post, 28 ins. long, 2½ ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 89° 50' E., 100.9 lks. dist., with brass cap mkd. RM E 1/16 S13 66.6 FT TO COR 1989 and an arrow pointing to the corner.

Corner is located near head of draw, drains S. 80° W., at SW. cor. of logged area.

From this point, a point established as the E 1/16 sec. cor. of secs. 12 and 13 by Reid in 1958, and recorded in Lane County Reestablishment No. 2187, bears N. 84¼° E., 0.088 chs. dist., monumented with a brass tablet, 3 ins. diam., set flush in sandstone bedrock, mkd. 1/16 12 13 USFS 1958. This point was not established by a registered surveyor/engineer and is not utilized in this survey.

From this same point, a point established as the E 1/16 sec. cor. of secs. 12 and 13 by Baker in 1988, recorded in Douglas County Survey Map 107-1, and corrected by Baker in 1989, recorded in Douglas County Survey Map 110-15, bears S. 34½° E., 0.035 chs. dist., monumented with a railroad spike, set flush in sandstone bedrock.

S. 89° 06' 00" W., beginning new measurement.

Descend broken W. slope, through timber.

19.665

The ¼ sec. cor. of secs. 12 and 13, reestablished by proportionate measurement by Daniel W. Baker, Registered Land Surveyor No. 1978, in 1989, recorded in Douglas County Survey Map 110-15, and is accepted as the corner; monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, in a collar of stone, with aluminum cap mkd.

T19S R10W  
¼ S 12  
¼ S 13  
PLS 1978  
1988

from which the bearing trees mkd. by Baker in 1988, recorded in Douglas County Map 107-1 and reused in Douglas County Survey Map 110-15

A hemlock, 12 ins. diam., bears S. 86° E., 22½ lks. dist., with scribe marks ¼ S12 BT visible on unhealed double blaze.

A hemlock, 10 ins. diam., bears S. 32¾° E., 55 lks. dist., with scribe marks ¼ S13 BT visible on unhealed double blaze.

From this point, a point established as the ¼ sec. cor. of secs. 12 and 13 by Alan D. Reid, U.S. Forest Service Forester, in 1958, and recorded in Lane County Reestablishment No. 2187, bears N. 48° 50' E., 0.181 chs. dist. This point was not reestablished by a registered land surveyor/engineer and is not utilized in this survey, determined from the bearing trees mkd. by Reid:

A hemlock stump, 18 ins. diam., 6 ft. high, bears N. 51¾° W., 50 lks. dist., with scribe marks FS ¼ BT visible on partially healed blaze.

A fir stump, 30 ins. diam., 7 ft. high, bears N. 2° W., 51 lks. dist., with scribe marks S12 ¼ FS visible on partially healed blaze.