

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

18781

CHAINS

From this same point, a point established as the $\frac{1}{4}$ sec. cor. of secs. 12 and 13 by Baker in 1988, recorded in Douglas County Survey Map 107-1, and corrected by Baker in 1989, recorded in Douglas County Survey Map 110-15, bears S. $51^{\circ} 50'$ E., 0.095 chs. dist., monumented with an iron rod, $\frac{5}{8}$ in. diam., firmly set, projecting 2 ins. above ground.

Also from this same point, United States Forest Service GPS Station No. 191013, bears S. $47^{\circ} 59' 30''$ W., 24.933 chs. dist., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set flush with ground surface, with aluminum cap mkd. GPS 191013 + 1988.

S. $89^{\circ} 08' 00''$ W., beginning new measurement.

Ascend broken NE. slope, through logged area.

39.315 The cor. of secs. 11, 12, 13 and 14.

From the cor. of secs. 26, 27, 34 and 35, perpetuated by Milo E. Godfrey, Registered Land Surveyor No. 496, in 1964, and recorded in Douglas County Corner Renewal No. 1, and perpetuated by Gregroy E. Quibell, Registered Land Surveyor No. 1834, in 1982, and recorded in Douglas County Corner Renewal No. 32.; monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T19S	
S 27	S 26
S 34	S 35
R10W	
1982	
1964	

from which the remains of the original bearing trees

A fir, 47 ins. diam., bears N. 58° E., 54 lks. dist., with two healed blazes.

A fir, 40 ins. diam., bears S. 7° E., 19 lks. dist., with two healed blazes. (Record, S. 70° E.)

A fir, 39 ins. diam., bears S. 64° W., 18 lks. dist., with two healed blazes.

A fir snag, 28 ins. diam., 6 ft. high, bears N. 59° W., 8 lks. dist., with fragmentary scribe marks visible on opened blaze.

and a bearing tree mkd. by Godfrey

A hemlock, 15 ins. diam., bears N. $29\frac{1}{2}^{\circ}$ E., 136 lks. dist., with healed double blaze.

Corner is located in a barbed wire fence, bears N. and S.

N. $1^{\circ} 40' 00''$ W., bet. secs. 26 and 27.

Descend gradual NE. slope, along and near barbed wire fence, through timber, posting true line.

8.80 Fence, barbed wire, bears N. 50° W. and S. 50° E., 20 lks. dist., to fence corner.

9.20 U.S. Forest Service Road No. 23, asphalt, 30 lks. wide, bears N. 50° W. and S. 50° E.

9.50 Fence, barbed wire, bears N. 60° W. and S. 60° E.

13.35 Plastic water pipe, 3 ins. diam., lying on ground, bears E. and W.