

County Surveyor's Record, Douglas County, Oregon

18782

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS													
15.30	Left bank North Fork Smith River, bears N. 80° W. and S. 80° E., 130 lks. wide, course N. 80° W.												
16.60	Right bank North Fork Smith River, bears N. 80° W. and S. 80° E., and base of rock bluff; asc. steep S. slope.												
22.590	<p>Point for the S 1/16 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td></td> <td style="padding: 0 5px;">S 1/16</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S 27</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 26</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">1989</td> <td></td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 23 ins. diam., bears S. 47° E., 25 lks. dist., mkd. S 1/16 S26 BT.</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 28 ins. in the ground, for a reference monument, bears N. 87° 38' W., 92.4 lks. dist., with brass cap mkd. RM S 1/16 S27 61.0 FT TO COR 1989 and an arrow pointing to the corner.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as a working S 1/16 sec. cor. of secs. 26 and 27, by a U.S. Forest Service cutting boundary agreement survey in 1977, reord held at the Mapleton Ranger Station, bears S. 14° 03' E., 2.649 chs. dist., monumented with a ¼ in. angle iron, firmly set, projecting 24 ins. above ground, from which the bearing trees mkd. in 1977:</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears N. 86½° E., 29 lks. dist., with an aluminum tag.</p> <p style="margin-left: 40px;">A fir, 21 ins. diam., bears N. 70½° W., 24 lks. dist., with an aluminum tag.</p> <p>Ascend S. slope.</p>		S 1/16		S 27		S 26		1989				
	S 1/16												
S 27		S 26											
	1989												
28.10	Ridge, bears E. and W.; desc. N. slope.												
30.20	U.S. Forest Service Road No. 48-922, gravel, 25 lks. wide, bears N. 80° W. and S. 60° E., in a curve.												
36.90	Peach Creek, 5 lks wide, course S. 80° W.; asc. SE. changing to SW. slope.												
45.180	<p>Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td></td> <td style="padding: 0 10px;">T19S</td> <td style="padding: 0 10px;">R10W</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td></td> </tr> <tr> <td></td> <td style="padding: 0 5px;">1989</td> <td></td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears N. 23½° E., 37½ lks. dist., mkd. ¼ S26 BT.</p> <p style="margin-left: 40px;">A fir, 27 ins. diam., bears N. 31° W., 31 lks. dist., mkd. ¼ S27 BT.</p>		T19S	R10W		S 27	S 26					1989	
	T19S	R10W											
	S 27	S 26											
	1989												