

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

18783

CHAINS

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a local $\frac{1}{4}$ sec. cor. of secs. 26 and 27, bears S. $23^{\circ} 27'$ E., 3.128 chs. dist., determined from the information found on tags nailed to purported original bearing trees and corner recovery cards held at Mapleton Ranger Station:

A fir snag, 14 ins. diam., 40 ft. high, bears S 9° E.,
17 lks. dist., with chop and saw marks to wind break
pitch seam on 4-in. core diam., on N. side.

A fir, 26 ins. diam., bears S., $7\frac{1}{2}$ lks. dist., with scar
and an aluminum tag on N. side.

A fir, 33 ins. diam., bears N. 6° W., 11 lks. dist.,
with chop marks on SW. side.

Ascend SW. slope.

48.90 U.S. Forest Service Road No. 48, asphalt, 25 lks. wide, bears
S. 80° E. and S. 70° W., in a curve; asc. broken S. slope.

78.00 Same road, gravel, 25 lks. wide, bears N. 60° E. and N. 80° W., in
a curve; desc. broken N. slope.

90.360 Point for the cor. of secs 22, 23, 26 and 27, at proportionate
distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in
the ground, with brass cap mkd:

T19S	R10W
S 22	S 23
S 27	S 26
1989	

from which

A cedar, 16 ins. diam., bears N. 18° E., 125 lks. dist.,
mkd. T19S R10W S23 BT.

A cedar, 18 ins. diam., bears S. 55° E., $34\frac{1}{2}$ lks. dist.,
mkd. T19S R10W S26 BT.

A hemlock, 32 ins. diam., bears S. $44\frac{1}{2}^{\circ}$ W., 45 lks. dist.,
mkd. T19S R10W S27 BT.

A hemlock, 23 ins. diam., bears N. $65\frac{1}{2}^{\circ}$ W., 130 lks. dist.,
mkd. T19S R10W S22 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the cor. of secs. 10, 11, 14 and 15 bears N. $2^{\circ} 52'$
 $30''$ E., 180.865 chs. dist., perpetuated by Donald L. Peel,
Registered Land Surveyor No. 752, in 1980, and recorded in Lane
County Survey No. 24,151; monumented with an aluminum post, $2\frac{1}{2}$ ins.
diam., firmly set in the root hole of the original corner tree,
projecting 1 in. above ground, with aluminum cap mkd.

T19S	R10W
S 10	S 11
S 15	S 14
PLS 752	
1980	

from which the remains of the original bearing trees

A cedar, 18 ins. diam., bears N. 26° E., 34 lks. dist.,
with healed blaze. (Record, 40 lks.)