

County Surveyor's Record, Douglas County, Oregon 20

18784

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears S. 40° E., 3 lks. dist., lying alongside is a fir, 12 ins. diam., with scribe marks T19S R10W S14 BT visible on opened blaze.

A hemlock, 16 ins. diam., bears S. 89° W., 39 lks. dist., with chop marks. (Record, S. 83° W., 40 lks.)

and the bearing trees mkd. by Peel

A fir, 32 ins. diam., bears S. 88° E., 58 lks. dist., with healed double blaze.

A cedar, 52 ins. diam., bears S. 38¾° W., 19 lks. dist. with scribe marks T19S R10W S15 BT visible on partially healed double blaze.

A cedar, 23 ins. diam., bears N. 39¾° W., 74 lks. dist., with scribe marks T19S R10W S10 BT visible on partially healed double blaze.

Lying down the hill is the remnants of the original corner tree, a fir, 12 ins. diam., with scribe marks O and S10 in reverse and relief visible.

Corner is located on a N. 20° E. slope, in timber.

This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered.

From the cor. of secs. 26, 27, 34 and 35.

N. 89° 01' 30" W., bet. secs. 27 and 34.

Over nearly level land sloping N., timber to N., logged area to S., posting true line.

6.40 Enter timber, edge bears E. and S. 50° W.

13.00 Creek, 2 lks. wide, course N. 60° W.

19.835 The E 1/16 sec. cor. of secs. 27 and 34, established by Gordon H. Long, Registered Land Surveyor No. 1017, in 1877, recorded in Douglas County Survey Map 65-63, and is accepted as the corner; monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

T19S R10W
E 1/16 $\frac{S\ 27}{S\ 34}$
PLS 1017
1977

from which the bearing trees mkd. by Long

A fir, 25 ins. diam., bears S. 76¾° W., 85 lks. dist., with healed double blaze.

A fir, 55 ins. diam., bears N. 34° W., 82 lks. dist., with healed double blaze.

and a new accessory

A stainless steel psot, 28 ins. long, 2½ ins. diam., set 28 ins. in the ground, for a reference monument, bears N. 2° 32' W., 76.5 lks. dist., with brass cap mkd. RM E 1/16 S27 50.5 FT TO COR 1989 and an arrow pointing to the corner.

N. 89° 03' 00" W., beginning new measurement.