

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

18785

CHAINS

- Over level land.
- 0.30 Toe of hill, bears N. 70° W. and S. 70° E.; asc. NE. slope.
- 2.90 Spur, slopes N. 50° W.; desc. SW. slope.
- 7.00 Bottom of descent; over nearly level land.
- 12.70 Left bank North Fork Smith River, bears N. 40° E. and S. 40° W., 150 lks. wide, course S. 40° W.
- 14.60 Right bank of North Fork Smith River, bears N. 40° E. and S. 40° W.; asc. SE. slope.
- 15.30 Top of riverbank, bears NE. and SW.; over nearly level land.
- 18.20 U.S. Forest Service Road No. 48, gravel, 30 lks. wide, bears N. 30° E. and S. 40° W., in a curve, logged area to S.
- 19.00 Toe of hill, bears NE. and SW.; asc. SE. slope.
- 19.845 The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, perpetuated by Gordon H. Long, Registered Land Surveyor No. 1017, in 1977, and recorded in Douglas County Survey Map 65-63, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
- T19S R10W
 $\frac{1}{4}$ S 27
 $\frac{1}{4}$ S 34
PLS 1017
1977
- from which the remains of the original bearing trees
- A fir snag, 72 ins. diam., 5 ft. high, bears S. 58° W., 57 lks. dist., no marks visible. (Record, S. 55° W., 75 lks.)
- An alder snag, 18 ins. diam., 2 ft. high, bears N. 8° W., 20 lks. dist., no marks. (Record, 19 lks.)
- and the bearing trees mkd. by Long
- A maple, 28 ins. diam., bears S. 84° E., 47 lks. dist., with scribe marks visible in partially healed blaze.
- A fir, 55 ins. diam., bears N. 22° W., 53 lks. dist., with healed double blaze.
- From this point, United States Forest Service GPS Station No. 191034, bears S. 2° 38' 50" W., 19.837 chs. dist., monumented with an aluminum post, 2 $\frac{1}{2}$ ins. diam., firmly set, flush with ground surface, with aluminum cap mkd. GPS 191034 + 1988.
-
- S. 89° 52' 30" W., beginning new measurement.
- Ascend SE. slope.
- 7.70 Spur, slopes S.; desc. SW. slope.
- 15.90 Toe of hill, bears N. and S.; over swampy area with creek, course S.
- 16.60 Toe of hill, bears N. and S.; asc. E. slope.
- 21.50 Spur, slopes S.; desc. W. slope.
- 25.20 U.S. Forest Service Road No. 4820, gravel, 20 lks. wide, bears N. 50° E. and S. 40° W., in a curve; enter timber.