

County Surveyor's Record, Douglas County, Oregon

18788

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

from which the bearing trees mkd. by Peel

A fir, 36 ins. diam., bears N. $9\frac{1}{4}^{\circ}$ E., 63 lks. dist.,
with healed double blaze.

A hemlock, 37 ins. diam., bears S. 15° E., 72 lks. dist.,
with scribe marks t19S R10W S15 BT visible on partially
healed double blaze.

A fir, 41 ins. diam., bears S. $30\frac{1}{2}^{\circ}$ W., 51 lks. dist.,
with healed double blaze.

A hemlock, 17 ins. diam., bears N. 27° W., 26 lks. dist.,
with illegible scribe marks visible on partially healed
double blaze.

Alongside the aluminum post is the original sandstone, 16 x 8 x 6
ins., no marks visible.

Corner is located on a spur, slopes N. 10° W., in timber.

From the cor. of secs. 9, 10, 15 and 16, the United States Forest
Service GPS Station No. 191016, bears S. $71^{\circ} 06' 40''$ W., 22.811 chs.
dist., monumented with an aluminum tablet, $3\frac{1}{4}$ ins. diam., firmly set
in concrete flush with ground surface, mkd. CAMERA POINT NO. 191016
1985.

This control line was fully retraced and careful search was made for
evidence of intervening corners, none of which was recovered.

From the cor. of secs. 22, 23, 26 and 27.

N. $89^{\circ} 08' 00''$ W., bet. secs. 22 and 27.

Descend N. changing to NW. slope, through timber.

3.30 Creek, 2 lks. wide, course S. 20° W.; asc. broken E. slope.

22.00 Ravine, drains S. 30° W.; asc. SE. slope.

24.70 Spur, slopes N. 30° E.; desc. broken W. slope.

31.50 Top of ascent, slopes S.; desc. SW. changing to W. slope.

38.055 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate
distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in
the ground, with brass cap mkd:

T19S	R10W
$\frac{1}{4}$	<u>S 22</u>
	S 27
	1989

from which

A cedar, 16 ins. diam., bears S. $34\frac{1}{4}^{\circ}$ E., 82 lks. dist.,
mkd. $\frac{1}{4}$ S27 BT.

A fir, 49 ins. diam., bears N. 46° W., $78\frac{1}{2}$ lks. dist.,
mkd. $\frac{1}{4}$ S22 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel
post.

From this point, the United States Forest Service GPS Station No.
191022, bears N. $32^{\circ} 14' 30''$ W., 17.833 chs. dist., monumented with
an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set flush with ground
surface, with aluminum cap mkd. GPS 191022 + 1988.