

# County Surveyor's Record, Douglas County, Oregon

25

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 19 S., R. 10 W., Willamette Meridian, Oregon

18789

CHAINS	
	Descend W. slope.
39.40	Creek, 4 lks. wide, course S.; asc. broken E. slope, enter logged area.
76.110	The cor. of secs. 21, 22, 27 and 28.
	<hr/> From the cor. of secs. 27, 28, 33 and 34. S. 88° 21' 00" W., bet. secs. 28 and 33.  Over nearly level land, through timber.
15.10	Spur, slopes S. 10° E.; desc. broken W. slope.
23.10	Spur, slopes S. 10° E.; desc. broken SW. slope.
29.690	The W-E 1/64 sec. cor. of secs. 28 and 33 established by Donald L. Peel, Registered Land Surveyor No. 752, in 1980, recorded in Douglas County Survey Map 85-46, and is accepted as the corner; monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 1 in. above ground, with aluminum cap mkd.
	T19S    R10W W-E 1/64 $\frac{S \ 28}{S \ 33}$ PLS 752 1980
	from which the bearing trees mkd. by Peel
	A fir, 40 ins. diam., bears S. 86° W., 95 lks. dist., with healed blaze.
	A fir, 8 ins. diam., bears N. 31½° W., 72 lks. dist., with healed blaze.
	<hr/> S. 88° 19' 30" W., beginning new measurement.
	Over S. slope.
1.50	Begin descending SW. slope.
9.00	Creek, 1 lk. wide, course S. 50° W.; asc. SE. slope.
9.890	The ¼ sec. cor. of secs. 28 and 33, perpetuated by Ernesto R. Alvarado, for the Douglas County Surveyor's Office, in 1978, and recorded in Douglas County Corner Renewal No. 21, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	T19S    R10W ¼ $\frac{S \ 28}{S \ 33}$ 1978
	from which the remaining original bearing tree
	A fir, 55 ins. diam., bears N. 71° E., 11 lks. dist., with scribe mark S visible on chopped open blaze on 14 in. core diam.
	and the bearing tree mkd. by Alvarado
	A fir, 32 ins. diam., bears N. 82° W., 27 lks. dist., with healed double blaze.
	Corner is located on a spur, slopes S. 30° W.