

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

27

18791

CHAINS

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Descend broken NE. slope.

51.00 Paxton Creek, 10 lks. wide, course S. 80° E.; asc. broken SE. slope.

90.460 Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:

T19S	R10W
S 20	S 21
S 29	S 28
1989	

from which

A fir, 7 ins. diam., bears N. 76° E., 21 lks. dist.,
mkd. T19S R10W S21 BT.

A fir, 6 ins. diam., bears S. 77° E., 12½ lks. dist.,
mkd. T19S R10W S28 BT.

A fir, 10 ins. diam., bears S. 21° W., 17 lks. dist.,
mkd. T19S R10W S29 BT.

A fir, 8 ins. diam., bears N. 6° W., 9½ lks. dist.,
mkd. T19S R10W S20 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Corner is located on an E. slope in logged area.

From this point, the United States Forest Service GPS Station No. 191021, bears N. 10° 05' 30" E., 17.660 chs. dist., monumented with an aluminum post, 2½ ins. diam., firmly set in concrete flush with ground surface, with aluminum cap mkd. GPS 191021 + 1988.

From this same point, the cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp., bears N. 83° 11' 30" W., 158.790 chs. dist., perpetuated by Everett Mitchell of the Lane County Surveyor's Office, in 1976, and recorded in Lane County Reestablishment No. 6104, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T19S	
R11W	R10W
S 24	S 19
S 25	S 30
1976	

from which the remains of the original bearing trees

A fir, 33 ins. diam., bears S. 45° E., 64 lks. dist.,
with healed blaze. (Record, 62 lks.)

A fir snag stump, 48 ins. diam., bears N. 47° W.,
157 lks. dist., no marks visible. (Record, 154 lks.)

the remains of bearing trees mkd. by Collier and Strickler

An alder stump, 18 ins. diam., bears S. 38° E., 5 lks.
dist., no marks.

A fir stump, 37 ins. diam., bears S. 39° W., 60 lks.
dist., with healed blaze. (Record, S. 41¼° W.)