

County Surveyor's Record, Douglas County, Oregon 30

18794

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set a brass tablet, 3¼ ins. diam., 3½ in. stem, in drill hole in sandstone ledge near base of road cutbank, with top mkd.</p> <p style="text-align: center;">T19S R10W ¼ <u>S 21</u> ✓ S 28 1989</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 49¼° E., 51 lks. dist., mkd. ¼ S21 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 62¼° W., 308½ lks. dist., mkd. ¼ S28 BT.</p> <p>Descend over road cutbank.</p>
38.25	Base of road cutbank, bears NE. and SW.; over roadbed.
38.65	U.S. Forest Service Road No. 4820, gravel, 25 lks. wide, bears N. 20° E. and S. 50° W., in a curve; desc. broken NW. slope.
55.50	U.S. Forest Service Road No. 4820-951, gravel, 20 lks. wide, bears N. 20° E. and S. 30° W., in a curve; asc. broken E. slope, through timber.
76.280	The cor. of secs. 20, 21, 28 and 29.
<p>Subdivision of Section 13, T. 19 S., R. 10 W., Willamette Meridian, Oregon</p>	
	<p>From the ¼ sec. cor. of secs. 13 and 24.</p> <p>N. 3° 45' 00" E., on the N. and S. center line of sec. 13.</p> <p>Ascend S. slope through logged area, posting true line.</p>
3.60	Spur, slopes S. 50° E.; desc. NE. slope.
8.70	Overgrown rock road, 15 lks. wide, bears N. 50° W. and S. 50° E.
9.80	Ravine, drains N. 80° E.; asc. E. slope.
12.20	East shoulder of same road, bears N. 30° E. and S. 40° W.; along road.
15.00	Leave same road, shoulder bears N. 10° W. and S. 10° E.; desc. E. slope.
18.20	Same road, bears N. 30° E. and S. 30° W.; asc. broken E. slope.
23.160	Point for the center S 1/16 sec. cor. of sec. 13.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, over a nail driven into a tree root and in a mound of stone, 2 ft. base, to top, with brass cap mkd:</p> <p style="text-align: center;"> C S 1/16 S 13 C 1989</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 28 ins. in the ground, for a reference monument, bears N. 88° 12' E., 76.9 lks. dist., with brass cap mkd. RM CS 1/16 S13 50.7 FT TO COR 1989 and an arrow point to the corner.</p>