

County Surveyor's Record, Douglas County, Oregon 31

Subdivison of Section 13,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

18795

CHAINS	
	<p style="text-align: center;">A fir, 10 ins. diam., bears S. $61\frac{1}{2}^\circ$ W., $55\frac{1}{2}$ lks. dist., mkd. CS 1/16 S13 BT.</p> <p>Corner is located near an E. and W. timber cutting line.</p> <p>From this point, a point established as an approximate center S 1/16 sec. cor. of sec. 13 by C.W. Worthylake et al., employees of Davidson Industries, Inc., in 1968, record held by Davidson Industries, Inc., Mapleton, Oregon, bears S. $87^\circ 30'$ W., 1.633 chs. dist., determined from the bearing tree mkd. by Worthylake et al:</p> <p style="text-align: center;">A cedar, 22 ins. diam., bears N. $41\frac{1}{2}^\circ$ W., $14\frac{1}{2}$ lks. dist., with healed blaze.</p> <p>Ascend S. slope; enter timber.</p>
32.20	<p>Divide between Siuslaw and Smith River drainages, bears N. 70° E. and S. 70° W.; desc. N. changing to NW. slope, through logged area.</p>
36.60	<p>U.S. Forest Service Road No. 4890, gravel, 25 lks. wide, bears N. 50° E. and S. 40° W., in a curve; desc. broken NW. slope.</p>
41.20	<p>Spur, slopes N. 60° W.; desc. broken NW. slope.</p>
45.90	<p>Spur, slopes N. 60° W.; desc. NE. slope.</p>
46.320	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 13, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd:</p> <div style="text-align: center; margin: 10px 0;"> <p>T19S R10W C$\frac{1}{4}$ S 13 1989</p> </div> <p>from which</p> <p style="text-align: center;">A fir, 27 ins. diam., bears S. $55\frac{1}{2}^\circ$ E., 75 lks. dist., mkd. C$\frac{1}{4}$ S13 BT.</p> <p style="text-align: center;">A hemlock, 11 ins. diam., bears S. $18\frac{1}{2}^\circ$ W., $21\frac{1}{2}$ lks. dist., mkd. C$\frac{1}{4}$ S13 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend broken NE. slope through timber.</p>
92.700	<p>The $\frac{1}{4}$ sec. cor. of secs. 12 and 13.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the $\frac{1}{4}$ sec. cor. of sec. 13 only, on the E. bdy. of the Tp. S. $89^\circ 34' 00''$ W., on the E. and W. center line of sec. 13.</p> <p>Ascend S. slope, through logged area, posting line.</p>
3.70	<p>Creek, 1 lk. wide, course S. 70° E., at 30 ft. high waterfall; asc. NE. changing to E. slope.</p>
11.60	<p>Corner of timber, edge bears N. and W.</p>
19.365	<p>Point for the center E 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, to bedrock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd:</p> <div style="text-align: center; margin: 10px 0;"> <p>C $\frac{E}{S}$ $\frac{1/16}{13}$ C 1989</p> </div>